

INDUSTRIAL COMPONENT DATA

ESWB04 EPDU SW 0U (309 16A 1P)20XC13:4XC19 EATON ELECTRIC Eaton Switched Rack PDU, 0U, 36U, Inputs IEC-60309..

Brand: EATON - MOELLER | Manufacturer Part Number: ESWB04



Manufacturer	EATON - MOELLER
MPN / Reference	ESWB04
Catalog number	EPDU SW 0U (309 16A 1P)20XC13:4XC19
Category	Power distribution unit (PDU)
Minimum order	1 Pcs
Document ID	EO-1B52B0167C
Generated	2026-08-05

Product Overview

Eaton Switched Rack PDU, 0U, 36U, Inputs IEC-60309 16A 1Ph, 3.84 kW max, 16A, 200-240V, Outlets 20XC13 : 4XC19 EPDU SW 0U (309 16A 1P)20XC13:4XC19

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Single-phase UPS up to 11kVA**

Additional Product Information

Eaton Switched Rack PDU, 0U, 36U, Inputs IEC-60309 16A 1Ph, 3.84 kW max, 16A, 200-240V, Outlets 20XC13 : 4XC19 Eaton Switched Rack PDU, 0U, 36U, Inputs IEC-60309 16A 1Ph, 3.84 kW max, 16A, 200-240V, Outlets 20XC13 : 4XC19 Remote Site Management.

Turn off unused outlets to control commissioning.

Phase Metering, Circuit Breaker Current Metering and Input Metering.

Circuit Breaker Status Monitoring.

Outlet and IT Equipment Switching/reboot /sequencing across A and B feed in Daisy-Chain.

Sequence Outlets to avoid in-rush current, to ensure equipment starts in correct order.

Hot-Swap Control module with advanced LCD.

Optional Temperature/Humidity sensor.

Built-in IEC outlet eGrip retention, retains all standard IEC plugs.

Daisy-Chain up to 8 ePDUs, reduce network infrastructure costs.

Power chain monitoring & Real time Intelligence on your Data Center, via Eaton Intelligent Power Manager Infrastructure.
Delivery program

TypeRack PDUIInput ConnectionIEC-60309 16A 1PhCord Length3mInput Voltage200-240VPhaseSingle-phaseFrequency
Rating50/60 HzEthernet InterfaceYesSerial InterfaceYesForm Factor0U (Vertical)Outlet ControlYesOperating
Temperature0° to 60°C (32° to 140°F)Outlets20XC13 : 4XC19Number of Outputs C1320Number of Outputs
C194Amperage Rating16AMounting DirectionVerticalETIM ClassEC002762ePDU General Prod Spec1Fitted With:Display
Mounting material
Ampere MeterePDU Other Prod SpecElectrical ConnectionConnecting cord with plugEvaluationAt distanceMounting
Dimension (metrical)52Mounti...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / ESWB04 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.