

## INDUSTRIAL COMPONENT DATA

# ESWB05 EPDU SW 0U (309 32A 1P)20XC13:4XC19 EATON ELECTRIC Eaton Switched Rack PDU, 0U, 36U, Inputs IEC-60309..

Brand: EATON - MOELLER | Manufacturer Part Number: ESWB05



|                 |                                     |
|-----------------|-------------------------------------|
| Manufacturer    | EATON - MOELLER                     |
| MPN / Reference | ESWB05                              |
| Catalog number  | EPDU SW 0U (309 32A 1P)20XC13:4XC19 |
| Category        | Power distribution unit (PDU)       |
| Minimum order   | 1 Pcs                               |
| Document ID     | EO-92C0F7386F                       |
| Generated       | 2026-08-06                          |

## Product Overview

Eaton Switched Rack PDU, 0U, 36U, Inputs IEC-60309 32A 1Ph, 7.4 kW max, 32A, 200-240V, Outlets 20XC13 : 4XC19  
EPDU SW 0U (309 32A 1P)20XC13:4XC19

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                |
|--------------|------------------------------------------------|
| Catalog path | EATON - MOELLER > Single-phase UPS up to 11kVA |
|--------------|------------------------------------------------|

## Additional Product Information

Eaton Switched Rack PDU, 0U, 36U, Inputs IEC-60309 32A 1Ph, 7.4 kW max, 32A, 200-240V, Outlets 20XC13 : 4XC19  
Eaton Switched Rack PDU, 0U, 36U, Inputs IEC-60309 32A 1Ph, 7.4 kW max, 32A, 200-240V, Outlets 20XC13 : 4XC19  
Securely allows remote control and remote rebooting  
Highly secure with Admin controlling user access permission, password protection and SSL configurable to 1024 or 2048 bit  
Switch equipment on/off across both A and B feed (Requires Daisy Chained ePDUs)  
Sequence outlets to avoid in-rush current, to ensure equipment starts in correct order  
Input and Phase Metering, Circuit Breaker Current Metering  
IEC outlet eGrip plug retention: retains all standard IEC plugs  
60 Degree C operating temperature  
Colour-coded outlet and branch circuits for simple load balancing  
Eaton Hydraulic-Magnetic Circuit Breakers with accidental trip protection  
Low-profile form factor: 52mm wide x 53mm deep on most models

En masse configuration and update available via Intelligent Power Manager software

Single Pane Monitoring of many ePDUs+UPS as part of the power chain, & graceful Equipment shut down via Intelligent Power Manager software

Installation: Button mounting on rear & side + variable mounting system

[ Delivery program

ePDU General Prod Spec1 Fitted With: Ampere Meter

Display

Mounting material General Product Specifications Type Rack PDU ePDU Other Prod Spec Electrical Connection

Connecting cord with plug Evaluation At distance Mounting Dimension (metrical) 52 Mounting Dimension (...)

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / ESWB05 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.