

INDUSTRIAL COMPONENT DATA

ESWB22 EPDU SW 0U (C20 16A 1P)20XC13:4XC19 EATON ELECTRIC Eaton Switched Rack PDU, 0U, 36U, Inputs C20, 3.84..

Brand: EATON - MOELLER | Manufacturer Part Number: ESWB22



Manufacturer	EATON - MOELLER
MPN / Reference	ESWB22
Catalog number	EPDU SW 0U (C20 16A 1P)20XC13:4XC19
Category	Power distribution unit (PDU)
Minimum order	1 Pcs
Document ID	EO-1C850527FB
Generated	2026-08-04

Product Overview

Eaton Switched Rack PDU, 0U, 36U, Inputs C20, 3.84 kW max, 16A, 200-240V, Outlets 20XC13 : 4XC19
EPDU SW 0U (C20 16A 1P)20XC13:4XC19

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Single-phase UPS up to 11kVA
--------------	--

Additional Product Information

Eaton Switched Rack PDU, 0U, 36U, Inputs C20, 3.84 kW max, 16A, 200-240V, Outlets 20XC13 : 4XC19
Eaton Switched Rack PDU, 0U, 36U, Inputs C20, 3.84 kW max, 16A, 200-240V, Outlets 20XC13 : 4XC19
Securely allows remote control and remote rebooting

Highly secure with Admin controlling user access permission, password protection and SSL configurable to 1024 or 2048 bit
Switch equipment on/off across both A and B feed (Requires Daisy Chained ePDUs)

Sequence outlets to avoid in-rush current, to ensure equipment starts in correct order

Input and Phase Metering, Circuit Breaker Current Metering

IEC outlet eGrip plug retention: retains all standard IEC plugs

60 Degree C operating temperature

Colour-coded outlet and branch circuits for simple load balancing

Eaton Hydraulic-Magnetic Circuit Breakers with accidental trip protection

Low-profile form factor: 52mm wide x 53mm deep on most models

En masse configuration and update available via Intelligent Power Manager software

Single Pane Monitoring of many ePDUs+UPS as part of the power chain, & graceful Equipment shut down via Intelligent Power Manager software

Installation: Button mounting on rear & side + variable mounting system

Delivery program

Type Rack PDU Input Connection C20 Cord Length 3m Input Voltage 200-240V Phase Single-phase Frequency Rating 50/60 Hz Ethernet Interface Yes Serial Interface Yes Form Factor 0U (Vertical) Outlet Control Yes Operating Temperature 0° to 60°C (32° to 140°F) Outlets 20XC13 : 4XC19 Number of Outputs C13 20 Number of Outputs C...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / ESWB22 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.