

INDUSTRIAL COMPONENT DATA

EU1E-SWD-1XA-2 174720 Y7-174720 EATON ELECTRIC SmartWire-DT IP67 T-Connector analog module, one 0 20 mA anal..

Brand: EATON - MOELLER | Manufacturer Part Number: EU1E-SWD-1XA-2



Manufacturer	EATON - MOELLER
MPN / Reference	EU1E-SWD-1XA-2
Catalog number	Y7-174720
Category	Fieldbus, decentr. periphery - analogue I/O module
Minimum order	1 Pcs
Document ID	EO-CC91073A2A
Generated	2026-08-03

Product Overview

SmartWire-DT IP67 T-Connector analog module, one 0 - 20 mA analog output with power supply, one M12 I/O socket
EU1E-SWD-1XA-2

SmartWire-DT module with IP67 degree of protection, can be used to connect one analog output, 24 VDC 70 mA short-circuit proof sensor power supply, automatic address setting, 0 - 20 mA output, 12-bit resolution, short-circuit proof, I/O connection with M12 socket

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Smartwire Darwin
--------------	------------------------------------

Additional Product Information

General specifications

Product Name Eaton EU1E Analog module Catalog Number 174720 Model Code EU1E-SWD-1XA-2 EAN 4015081712069

Product Length/Depth 85.6 mm Product Height 20.1 mm Product Width 56.9 mm Product Weight 0.07 kg Certifications UL

UL File No.: E170645

CSA

IEC/EN 61131-2 Features & Functions

Electric connection type Screw connection Features Overload protection (sensor supply)

Fieldbus connection over separate bus coupler possible

Short-circuit protection (sensor supply)

Analog outputs configurable

Output, current

Output signal configurable

Analog inputs configurable Functions For connection of analog I/O signals General

Current consumption 67 mA, SmartWire-DT network

70 mA, Max. current consumption per M12 I/O plug, Sensor supply, SmartWire-DT network Degree of protection IP69K

NEMA 4X Mounting method Screw fixing (M4)

Mounting section (Clip M20)

Wall mounting/direct mounting

DIN rail

Rail mounting possible Overvoltage category II Pollution degree 3 Product category SmartWire-DT slave Repetition accuracy 0.5 % (Analog outputs) Type Voltage type DC Ambient conditions, mechanical

Constant acceleration 1 g, 8.4 - 150 Hz, according to IEC/EN 61131-2, Vibrations Constant amplitude 3,5 mm, 5 - 8.4 Hz, according to IEC/EN 61131-2, Vibrations Drop and topple 50 mm Drop height, Drop to IEC/EN 60068-2-31 Height of fall (IEC/EN 60068-2-32) - max 0.3 m Mounting position As required Shock resistance 30 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 11 ms,...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EU1E-SWD-1XA-2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.