

INDUSTRIAL COMPONENT DATA

EU2A-SWD-PBWN 174734 Y7-174734 EATON ELECTRIC Local branch SWDT, to gather local network with modules SWDT I..

Brand: EATON - MOELLER | Manufacturer Part Number: EU2A-SWD-PBWN



Manufacturer	EATON - MOELLER
MPN / Reference	EU2A-SWD-PBWN
Catalog number	Y7-174734
Category	Accessories/spare parts for controls
Minimum order	1 Pcs
Document ID	EO-78FE85CBA5
Generated	2026-08-06

Product Overview

Local branch SWDT, to gather local network with modules SWDT IP67

EU2A-SWD-PBWN

Eaton EU2A SWD accessories, Local SmartWire-DT branch

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Smartwire Darwin**

Additional Product Information

General specifications

Product Name Eaton EU2A Accessory Junction Catalog Number 174734 Model Code EU2A-SWD-PBWN EAN

4015081712205 Product Length/Depth 98 mm Product Height 20.1 mm Product Width 56.9 mm Product Weight 0.085 kg

Certifications EN 50178

IEC/EN 61131-2

IEC/EN 60529 Catalog Notes not relevant General

Degree of protection IP67 (according to IEC/EN 60529, EN 50178, VBG 4)

IP67 Mounting method Screw fixing (M5)

DIN rail

Mounting section (Clip M20) Overvoltage category II Pollution degree 3 Product category SmartWire-DT accessories Type Local SmartWire-DT branch Ambient conditions, mechanical

Constant acceleration 1 g, 8.4 - 150 Hz, according to IEC/EN 61131-2, Vibrations Constant amplitude 3,5 mm, 5 - 8.4 Hz, according to IEC/EN 61131-2, Vibrations Drop and topple 50 mm Drop height, Drop to IEC/EN 60068-2-31 Height of fall

(IEC/EN 60068-2-32) - max 0.3 m Mounting position As required Shock resistance 15 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 11 ms, 9 Impacts Climatic environmental conditions

Air pressure 795 - 1080 hPa (operation) Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min -40 °C Ambient storage temperature - max 70 °C Climatic proofing Damp heat, constant, to IEC 60068-2-3

Dry heat to IEC 60068-2-2 Environmental conditions Condensation: permissible Operating temperature - min -25 °C

Operating temperature - max 55 °C Electro magnetic compatibility

Air discharge....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EU2A-SWD-PBWN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.