

INDUSTRIAL COMPONENT DATA

EU2E-SWD-2PT 174733 Y7-174733 EATON ELECTRIC SmartWire-DT IP67 T-Connector analog module, two configurable P..

Brand: EATON - MOELLER | Manufacturer Part Number: EU2E-SWD-2PT



Manufacturer	EATON - MOELLER
MPN / Reference	EU2E-SWD-2PT
Catalog number	Y7-174733
Category	Fieldbus, decentr. periphery - analogue I/O module
Minimum order	1 Pcs
Document ID	EO-FBA81362FD
Generated	2026-08-03

Product Overview

SmartWire-DT IP67 T-Connector analog module, two configurable Pt100/Pt1000/Ni1000 temperature inputs, two M12 I/O sockets

EU2E-SWD-2PT

SWD module with IP69K degree of protection for connecting up to two temperature sensors, automatic address setting, PT100 temperature sensor parameterizable, pt1000, NI1000, scan time and averaging parameterizable, -50 °C to +400 °C temperature range, I/O connection with 2/3-wire configuration with M12 socket for each input

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Smartwire Darwin

Additional Product Information

General specifications

Product Name Eaton EU2E Analog module Catalog Number 174733 Model Code EU2E-SWD-2PT EAN 4015081712199

Product Length/Depth 98 mm Product Height 20.1 mm Product Width 56.9 mm Product Weight 0.085 kg Certifications IEC/EN 61131-2

UL

UL File No.: E170645

CSA Features & Functions

Electric connection type Screw connection Features Analog outputs configurable

Input signal, configurable

Fieldbus connection over separate bus coupler possible

Input, resistance thermometer

Analog inputs configurable Fitted with: Temperature sensors PT100, PT1000 and Ni1000

Display mode for temperatures (°C, °F, raw value) Functions For connection of analog I/O signals

Adjustable parameter settings General

Current consumption 37 mA, SmartWire-DT network Degree of protection IP69K

NEMA 4X Mounting method Rail mounting possible

Wall mounting/direct mounting

DIN rail

Mounting section (Clip M20)

Screw fixing (M4) Overvoltage category II Pollution degree 3 Product category SmartWire-DT slave Repetition accuracy 0.5 % (Temperature inputs) Type Analog modules Voltage type DC Ambient conditions, mechanical

Constant acceleration 1 g, 8.4 - 150 Hz, according to IEC/EN 61131-2, Vibrations Constant amplitude 3,5 mm, 5 - 8.4 Hz, according to IEC/EN 61131-2, Vibrations Drop and topple 50 mm Drop height, Drop to IEC/EN 60068-2-31 Height of fall (IEC/EN 60068-2-32) - max 0.3 m Mounting position As required Shock resistance 30 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 1...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EU2E-SWD-2PT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.