

INDUSTRIAL COMPONENT DATA

EU6E-SWD-4D4D-1 183266 Y7-183266 EATON ELECTRIC SWD Block module I/O module IP69K, 24 V DC, 4 inputs with po..

Brand: EATON - MOELLER | Manufacturer Part Number: EU6E-SWD-4D4D-1



Manufacturer	EATON - MOELLER
MPN / Reference	EU6E-SWD-4D4D-1
Catalog number	Y7-183266
Category	Fieldbus, decentr. periphery - digital I/O module
Minimum order	1 Pcs
Document ID	EO-BFDD5E40CC
Generated	2026-08-05

Product Overview

SWD Block module I/O module IP69K, 24 V DC, 4 inputs with power supply, 4 outputs with separate power supply, 4 M12 I/O sockets

EU6E-SWD-4D4D-1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Smartwire Darwin

Additional Product Information

General specifications

Product Name Eaton EU6E I/O module Catalog Number 183266 Model Code EU6E-SWD-4D4D-1 EAN 4015081781997

Product Length/Depth 34 mm Product Height 156.8 mm Product Width 60.8 mm Product Weight 0.25 kg Certifications CSA IEC/EN 61131-2

UL Catalog Notes with supply Features & Functions

Electric connection type Screw connection Features Fieldbus connection over separate bus coupler possible

Overload proof (with diagnostics)

Overload protection (sensor supply)

Short-circuit protection (sensor supply) Functions For connection of digital I/O signals

Short-circuit protection, outputs available General

Current consumption 66 mA, SmartWire-DT network, 24 V, without sensor and without I/O supply

70 mA, Max. current consumption per M12 I/O plug, Sensor supply, SmartWire-DT network Degree of protection IP69K

Mounting method Screw fixing (M4)

Wall mounting/direct mounting Overvoltage category II Pollution degree 3 Product category SmartWire-DT slave Residual ripple $\leq 5\%$ (input voltage) Type Digital modules Voltage type DC Ambient conditions, mechanical
Constant acceleration 1 g, 8.4 - 150 Hz, according to IEC/EN 61131-2, Vibrations Constant amplitude 3,5 mm, 5 - 8.4 Hz, according to IEC/EN 61131-2, Vibrations Drop and topple 50 mm Drop height, Drop to IEC/EN 60068-2-31 Height of fall (IEC/EN 60068-2-32) - max 0.3 m Mounting position As required Shock resistance 30 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 11 ms, 9 Impacts Climatic environme...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EU6E-SWD-4D4D-1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.