

INDUSTRIAL COMPONENT DATA

EU6E-SWD-4D4D-2 183267 Y7-183267 EATON ELECTRIC SWD Block module I/O module IP69K, 24 V DC, 4 inputs with po..

Brand: EATON - MOELLER | Manufacturer Part Number: EU6E-SWD-4D4D-2



Manufacturer	EATON - MOELLER
MPN / Reference	EU6E-SWD-4D4D-2
Catalog number	Y7-183267
Category	Fieldbus, decentr. periphery - digital I/O module
Minimum order	1 Pcs
Document ID	EO-25ECC24034
Generated	2026-08-04

Product Overview

SWD Block module I/O module IP69K, 24 V DC, 4 inputs with power supply, 4 outputs 2A with separate power supply, 4 M12 I/O sockets

EU6E-SWD-4D4D-2

SWD module with IP69K degree of protection for connecting 4 digital inputs and 4 digital outputs, sensor supply for each M12 socket: 24 VDC, 70 mA, short-circuit proof, automatic address setting, digital outputs 24 V DC 2A short-circuit proof, separate M22 connector for output supply, I/O connection with M12 sockets for two inputs/outputs

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Smartwire Darwin
--------------	------------------------------------

Additional Product Information

General specifications

Product Name Eaton EU6E I/O module Catalog Number 183267 Model Code EU6E-SWD-4D4D-2 EAN 4015081782000
Product Length/Depth 34 mm Product Height 156.8 mm Product Width 60.8 mm Product Weight 0.23 kg Certifications UL IEC/EN 61131-2

CSA Catalog Notes with supply Features & Functions

Electric connection type Screw connection Features Overload protection (sensor supply)

Short-circuit protection (sensor supply)

Fieldbus connection over separate bus coupler possible

Overload proof (with diagnostics) Functions Short-circuit protection, outputs available

For connection of digital I/O signals General

Current consumption 70 mA, Max. current consumption per M12 I/O plug, Sensor supply, SmartWire-DT network
66 mA, SmartWire-DT network, 24 V, without sensor and without I/O supply Degree of protection IP69K Mounting method
Wall mounting/direct mounting
Screw fixing (M4) Overvoltage category II Pollution degree 3 Product category SmartWire-DT slave Type Digital modules
Voltage type DC Ambient conditions, mechanical
Constant acceleration 1 g, 8.4 - 150 Hz, according to IEC/EN 61131-2, Vibrations Constant amplitude 3,5 mm, 5 - 8.4 Hz,
according to IEC/EN 61131-2, Vibrations Drop and topple 50 mm Drop height, Drop to IEC/EN 60068-2-31 Height of fall
(IEC/EN 60068-2-32) - max 0.3 m Mounting position As required Shock resistance 30 g, Mechanical, according to IEC/EN
60068-2-27, Half-sinusoidal shock 11 ms, 9 Impacts Climatic environmental conditions
Air pressure 795 - 108...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EU6E-SWD-4D4D-2 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.