

## INDUSTRIAL COMPONENT DATA

# EVG-2PHAS/4MODUL/HI 219573 Y7-219573 EATON ELECTRIC EV busbars 2Ph., 4.5HP, for auxiliary contact unit

Brand: EATON - MOELLER | Manufacturer Part Number: EVG-2PHAS/4MODUL/HI



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | EATON - MOELLER     |
| MPN / Reference | EVG-2PHAS/4MODUL/HI |
| Catalog number  | Y7-219573           |
| Category        | Phase busbar        |
| Minimum order   | 20 Pcs              |
| Document ID     | EO-C1D9CC51B3       |
| Generated       | 2026-08-03          |

## Product Overview

EV busbars 2Ph., 4.5HP, for auxiliary contact unit

EVG-2PHAS/4MODUL/HI

Eaton Moeller series xPole - Busbar. EV busbars 2Ph., 4.5HP, for auxiliary contact unit

Busbars: flashovers are minimized Use of end caps not required Saves 30% of the assembly time

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                               |
|--------------|---------------------------------------------------------------|
| Catalog path | EATON - MOELLER > Modular Switchgear - Others and Accessories |
|--------------|---------------------------------------------------------------|

## Additional Product Information

General specifications

Product Name Eaton Moeller series busbar Catalog Number 219573 Model Code EVG-2PHAS/4MODUL/HI EAN

9010238140202 Product Length/Depth 75.5 mm Product Height 30.9 mm Product Width 7.5 mm Product Weight 0.02 kg

Compliances RoHS conform Product specifications

Type Features Insulated Accessory/spare part type Busbar for residual current circuit breakers

Busbar for miniature circuit breaker

Busbar for combined residual current/power circuit breaker Electric connection type Fork Used with Busbar

EVG Rated surge voltage 4 KV Rated uninterrupted current (Iu) 63 A Suitable for number of devices 7 Number of poles

Two-pole Color Other Rated short-time withstand current (Icw) 0 kA Cross section 10 mm<sup>2</sup> Number of modular spacings 4

Number of phases 2 Pitch dimensions 0 mm Rated operational voltage (Ue) - max 500 V Rated conditional short-circuit

current (Iq) 25 kA Functions Busbar Suitable for Devices with auxiliary switch

2 devices

ETIM for 219573 Low-voltage industrial controls and switchgear (EC000215)

Feature Name

Feature Value

Number of phases (EF000351)

2

Number of poles (EF001391)

2

Suitable for number of devices (EF007241)

7

Module width (EF007504)

0 mm

Cross section (EF000649)

10 mm<sup>2</sup>

Length (EF001438)

75.5 mm

Can be cut to size (EF015250)

No

Width in number of modular spacings (EF002950)

4

Rated permanent current I<sub>u</sub> (EF001389)

63 A

Type of electric connection (EF003961)

Fork

Insulated (EF000019)

Yes

Rated surge voltage (EF002993)

4 kV

Conditioned rated short...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EVG-2PHAS/4MODUL/HI with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.