

INDUSTRIAL COMPONENT DATA

BUSBAR EVG-2PHAS 4AFDD 193378 Y7-193378 EATON ELECTRIC EVG-2PHAS/4AFDD

Brand: EATON - MOELLER | Manufacturer Part Number: BUSBAR EVG-2PHAS 4AFDD



Manufacturer	EATON - MOELLER
MPN / Reference	BUSBAR EVG-2PHAS 4AFDD
Catalog number	Y7-193378
Category	Phase busbar
Minimum order	10 Pcs
Document ID	EO-D15A49675F
Generated	2026-08-04

Product Overview

EVG-2PHAS/4AFDD

Eaton Moeller series busbar, BUSBAR EVG-2PHAS 4AFDD. Single-phase rail for 4 AFDD, 10mm²
EV busbars 2Ph., AFDD

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Enclosures

Additional Product Information

General specifications

Product Name Eaton Moeller series busbar Catalog Number 193378 Model Code BUSBAR EVG-2PHAS 4AFDD EAN 9010238019706 Product Length/Depth 192 mm Product Height 27.1 mm Product Width 9.5 mm Product Weight 0.06 kg
Compliances RoHS conform Product specifications

Features Insulated Electric connection type Fork Rated surge voltage 0 KV Rated uninterrupted current (Iu) 50 A Suitable for number of devices 0 Number of poles Three-pole Color Other Rated short-time withstand current (Icw) 12.5 kA 0 kA Cross section 10 mm² Number of modular spacings 28 Number of phases 4 Pitch dimensions 17.8 mm Rated operational voltage (Ue) - max 690 V Rated conditional short-circuit current (Iq) 25 kA 0 kA Suitable for 4 devices

Devices with N-busbar

ETIM for 193378 Low-voltage industrial controls and switchgear (EC000215)

Feature Name

Feature Value

Number of phases (EF000351)

4

Number of poles (EF001391)

3

Suitable for number of devices (EF007241)

0

Module width (EF007504)

17.8 mm

Cross section (EF000649)

10 mm²

Length (EF001438)

192 mm

Can be cut to size (EF015250)

No

Width in number of modular spacings (EF002950)

28

Rated permanent current I_u (EF001389)

50 A

Type of electric connection (EF003961)

Fork

Insulated (EF000019)

Yes

Rated surge voltage (EF002993)

0 kV

Conditioned rated short-circuit current I_q (EF001444)

25 kA

Max. rated operation voltage U_e (EF007357)

690 V

Rated short-time withstand current I_{cw} (EF007050)

0 kA

Suitable for devices with N-conductor (EF007218)

Yes....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BUSBAR EVG-2PHAS 4AFDD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.