

INDUSTRIAL COMPONENT DATA

EVG-2PHAS/4MODUL 268220 Y7-268220 EATON ELECTRIC Comb connection 2F, 4M, 63A for PLS. CLS. PKN., PFIM, PFHM,..

Brand: EATON - MOELLER | Manufacturer Part Number: EVG-2PHAS/4MODUL



Manufacturer	EATON - MOELLER
MPN / Reference	EVG-2PHAS/4MODUL
Catalog number	Y7-268220
Category	Phase busbar
Minimum order	20 Pcs
Document ID	EO-AA11F9744A
Generated	2026-08-05

Product Overview

Comb connection 2F, 4M, 63A for PLS. CLS. PKN., PFIM, PFHM, NWFP

EVG-2PHAS/4MODUL

Eaton Moeller series xPole - Busbar. EV busbars 2Ph., 4HP, 63A for PLS. CLS. PKN., PFIM, PFHM, PFNM

Busbars: flashovers are minimized Use of end caps not required Saves 30% of the assembly time

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Moeller series busbar Catalog Number 268220 Model Code EVG-2PHAS/4MODUL EAN 4015082682200 Product Length/Depth 27 mm Product Height 8 mm Product Width 65 mm Product Weight 0.02 kg

Compliances RoHS conform Product specifications

Type Features Insulated Accessory/spare part type Busbar for combined residual current/power circuit breaker

Busbar for miniature circuit breaker

Busbar for residual current circuit breakers Electric connection type Fork Used with Busbar

EVG Rated surge voltage 4 KV Rated uninterrupted current (Iu) 63 A Suitable for number of devices 2 Number of poles

Two-pole Color Other Rated short-time withstand current (Icw) 0 kA Cross section 10 mm² Number of modular spacings 4

Number of phases 2 Pitch dimensions 0 mm Rated operational voltage (Ue) - max 500 V Rated conditional short-circuit

current (Iq) 25 kA Functions Busbar Suitable for 2 devices

ETIM for 268220 Low-voltage industrial controls and switchgear (EC000215)

Feature Name

Feature Value

Number of phases (EF000351)

2

Number of poles (EF001391)

2

Suitable for number of devices (EF007241)

2

Module width (EF007504)

0 mm

Cross section (EF000649)

10 mm²

Length (EF001438)

27 mm

Can be cut to size (EF015250)

No

Width in number of modular spacings (EF002950)

4

Rated permanent current Iu (EF001389)

63 A

Type of electric connection (EF003961)

Fork

Insulated (EF000019)

Yes

Rated surge voltage (EF002993)

4 kV

Conditioned rated short-circuit current Iq (EF001444)

25 kA

Max....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EVG-2PHAS/4MODUL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.