

INDUSTRIAL COMPONENT DATA

EVG-3P+3N/12MODUL 121091 Y7-121091 EATON ELECTRIC 121091 EVG-3P+3N/12MODUL

Brand: EATON - MOELLER | Manufacturer Part Number: EVG-3P+3N/12MODUL



Manufacturer	EATON - MOELLER
MPN / Reference	EVG-3P+3N/12MODUL
Catalog number	Y7-121091
Category	Phase busbar
Minimum order	20 Pcs
Document ID	EO-9BC678F9FA
Generated	2026-08-04

Product Overview

121091 EVG-3P+3N/12MODUL

EVG-3P+3N/12MODUL

Eaton Moeller series xPole - Busbar. EV busbars 4Ph., 12HP, 3P+3N

Busbars: flashovers are minimized Use of end caps not required Saves 30% of the assembly time

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Moeller series busbar Catalog Number 121091 Model Code EVG-3P+3N/12MODUL EAN 4015081189212 Product Length/Depth 211 mm Product Height 28 mm Product Width 12 mm Product Weight 0.087 kg

Compliances RoHS conform Product specifications

Features Insulated Electric connection type Fork Rated surge voltage 4 kV Rated uninterrupted current (Iu) 63 A Suitable for number of devices 0 Number of poles Four-pole Color Other Rated short-time withstand current (Icw) 0 kA Cross section 10 mm² Number of modular spacings 12 Number of phases 4 Pitch dimensions 0 mm Rated operational voltage (Ue) - max 415 V Rated conditional short-circuit current (Iq) 25 kA Suitable for Devices with N-busbar

ETIM for 121091 Low-voltage industrial controls and switchgear (EC000215)

Feature Name

Feature Value

Number of phases (EF000351)

4
Number of poles (EF001391)
4
Suitable for number of devices (EF007241)
0
Module width (EF007504)
0 mm
Cross section (EF000649)
10 mm²
Length (EF001438)
211 mm
Can be cut to size (EF015250)
No
Width in number of modular spacings (EF002950)
12
Rated permanent current I_u (EF001389)
63 A
Type of electric connection (EF003961)
Fork
Insulated (EF000019)
Yes
Rated surge voltage (EF002993)
4 kV
Conditioned rated short-circuit current I_q (EF001444)
25 kA
Max. rated operation voltage U_e (EF007357)
415 V
Rated short-time withstand current I_{cw} (EF007050)
0 kA
Suitable for devices with N-conductor (EF007218)
Yes
Suitable for devices with auxiliary s...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EVG-3P+3N/12MODUL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.