

## INDUSTRIAL COMPONENT DATA

**EVG-3P+3N/16MODUL 105215 Y7-105215 EATON ELECTRIC  
EV busbars 4Ph., 16HP, 63A for PLS. CLS. PKN., PFIM,  
PFHM,..**

Brand: EATON - MOELLER | Manufacturer Part Number: EVG-3P+3N/16MODUL



|                 |                   |
|-----------------|-------------------|
| Manufacturer    | EATON - MOELLER   |
| MPN / Reference | EVG-3P+3N/16MODUL |
| Catalog number  | Y7-105215         |
| Category        | Phase busbar      |
| Minimum order   | 1 Pcs             |
| Document ID     | EO-983F65C5AC     |
| Generated       | 2026-08-05        |

**Product Overview**

EV busbars 4Ph., 16HP, 63A for PLS. CLS. PKN., PFIM, PFHM, PFNM

EVG-3P+3N/16MODUL

Eaton Moeller series xPole - Busbar. EV busbars 4Ph., 16HP, 63A for PLS. CLS. PKN., PFIM, PFHM, PFNM

Busbars: flashovers are minimized Use of end caps not required Saves 30% of the assembly time

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

Catalog path EATON - MOELLER &gt; Modular Switchgear - Others and Accessories

**Additional Product Information**

## General specifications

Product Name Eaton Moeller series busbar Catalog Number 105215 Model Code EVG-3P+3N/16MODUL EAN

4015081050123 Product Length/Depth 28 mm Product Height 12 mm Product Width 285 mm Product Weight 0.13 kg

Compliances RoHS conform Product specifications

Type Features Insulated Accessory/spare part type Busbar for residual current circuit breakers

Busbar for miniature circuit breaker

Busbar for combined residual current/power circuit breaker Electric connection type Fork Used with EVG

Busbar Rated surge voltage 4 kV Rated uninterrupted current (Iu) 63 A Suitable for number of devices 8 Number of poles

Four-pole Color Other Rated short-time withstand current (Icw) 0 kA Cross section 10 mm<sup>2</sup> Number of modular spacings 16

Number of phases 4 Pitch dimensions 0 mm Rated operational voltage (Ue) - max 415 V Rated conditional short-circuit

current (Iq) 25 kA Functions Busbar Suitable for 8 devices

Devices with N-busbar

ETIM for 105215 Low-voltage industrial controls and switchgear (EC000215)

Feature Name

Feature Value

Number of phases (EF000351)

4

Number of poles (EF001391)

4

Suitable for number of devices (EF007241)

8

Module width (EF007504)

0 mm

Cross section (EF000649)

10 mm<sup>2</sup>

Length (EF001438)

28 mm

Can be cut to size (EF015250)

No

Width in number of modular spacings (EF002950)

16

Rated permanent current Iu (EF001389)

63 A

Type of electric connection (EF003961)

Fork

Insulated (EF000019)

Yes

Rated surge voltage (EF002993)

4 kV

Conditioned rated short-circuit curr...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EVG-3P+3N/16MODUL with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.