

INDUSTRIAL COMPONENT DATA

EVG-3P+3N/18MODUL 274161 Y7-274161 EATON ELECTRIC EV busbars 4Ph., 18HP, 63A for PLS. CLS. PKN., PFIM, PFHM,..

Brand: EATON - MOELLER | Manufacturer Part Number: EVG-3P+3N/18MODUL



Manufacturer	EATON - MOELLER
MPN / Reference	EVG-3P+3N/18MODUL
Catalog number	Y7-274161
Category	Phase busbar
Minimum order	1 Pcs
Document ID	EO-9C58635C6A
Generated	2026-08-06

Product Overview

EV busbars 4Ph., 18HP, 63A for PLS. CLS. PKN., PFIM, PFHM, PFNM

EVG-3P+3N/18MODUL

Eaton Moeller series xPole - Busbar. EV busbars 4Ph., 18HP, 63A for PLS. CLS. PKN., PFIM, PFHM, PFNM

Busbars: flashovers are minimized Use of end caps not required Saves 30% of the assembly time

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Moeller series busbar Catalog Number 274161 Model Code EVG-3P+3N/18MODUL EAN

4015082741617 Product Length/Depth 27 mm Product Height 14 mm Product Width 323 mm Product Weight 0.163 kg

Compliances RoHS conform Certifications CE Product specifications

Type Features Insulated Accessory/spare part type Busbar for combined residual current/power circuit breaker

Busbar for residual current circuit breakers

Busbar for miniature circuit breaker Electric connection type Fork Used with EVG

Busbar Rated surge voltage 4 KV Rated uninterrupted current (Iu) 63 A Suitable for number of devices 9 Number of poles

Four-pole Color Other Rated short-time withstand current (Icw) 0 kA Cross section 10 mm² Number of modular spacings 18

Number of phases 4 Pitch dimensions 0 mm Rated operational voltage (Ue) - max 415 V Rated conditional short-circuit

current (Iq) 25 kA Functions Busbar Suitable for Devices with N-busbar

9 devices

ETIM for 274161 Low-voltage industrial controls and switchgear (EC000215)

Feature Name

Feature Value

Number of phases (EF000351)

4

Number of poles (EF001391)

4

Suitable for number of devices (EF007241)

9

Module width (EF007504)

0 mm

Cross section (EF000649)

10 mm²

Length (EF001438)

27 mm

Can be cut to size (EF015250)

No

Width in number of modular spacings (EF002950)

18

Rated permanent current Iu (EF001389)

63 A

Type of electric connection (EF003961)

Fork

Insulated (EF000019)

Yes

Rated surge voltage (EF002993)

4 kV

Conditioned rated...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EVG-3P+3N/18MODUL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.