

INDUSTRIAL COMPONENT DATA

EVG-4PHAS/8MODUL 215644 Y7-215644 EATON ELECTRIC Comb connection 4F, 8M, 63A for PLS. CLS. PKN., PFIM, PFHM,..

Brand: EATON - MOELLER | Manufacturer Part Number: EVG-4PHAS/8MODUL



Manufacturer	EATON - MOELLER
MPN / Reference	EVG-4PHAS/8MODUL
Catalog number	Y7-215644
Category	Phase busbar
Minimum order	10 Pcs
Document ID	EO-493F2B94FA
Generated	2026-08-04

Product Overview

Comb connection 4F, 8M, 63A for PLS. CLS. PKN., PFIM, PFHM, NWFP

EVG-4PHAS/8MODUL

Eaton Moeller series xPole - Busbar. EV busbars 4Ph., 8HP, 63A for PLS. CLS. PKN., PFIM, PFHM, PFNM

Busbars: flashovers are minimized Use of end caps not required Saves 30% of the assembly time

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Moeller series busbar Catalog Number 215644 Model Code EVG-4PHAS/8MODUL EAN

4015082156442 Product Length/Depth 140 mm Product Height 30 mm Product Width 10 mm Product Weight 0.083 kg

Compliances RoHS conform Product specifications

Type Features Insulated Accessory/spare part type Busbar for combined residual current/power circuit breaker

Busbar for miniature circuit breaker

Busbar for residual current circuit breakers Electric connection type Fork Used with EVG

Busbar Rated surge voltage 4 kV Rated uninterrupted current (Iu) 63 A Suitable for number of devices 2 Number of poles

Four-pole Color Other Rated short-time withstand current (Icw) 0 kA Cross section 10 mm² Number of modular spacings 8

Number of phases 4 Pitch dimensions 0 mm Rated operational voltage (Ue) - max 500 V Rated conditional short-circuit

current (Iq) 25 kA Functions Busbar Suitable for 2 devices

Devices with N-busbar

ETIM for 215644 Low-voltage industrial controls and switchgear (EC000215)

Feature Name

Feature Value

Number of phases (EF000351)

4

Number of poles (EF001391)

4

Suitable for number of devices (EF007241)

2

Module width (EF007504)

0 mm

Cross section (EF000649)

10 mm²

Length (EF001438)

140 mm

Can be cut to size (EF015250)

No

Width in number of modular spacings (EF002950)

8

Rated permanent current Iu (EF001389)

63 A

Type of electric connection (EF003961)

Fork

Insulated (EF000019)

Yes

Rated surge voltage (EF002993)

4 kV

Conditioned rated short-circuit curre...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EVG-4PHAS/8MODUL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.