

INDUSTRIAL COMPONENT DATA

EVGK-3PHAS/6MODUL EP-501075 Y7-501075 EATON ELECTRIC EVGK-3PHAS/6MODUL

Brand: EATON - MOELLER | Manufacturer Part Number: EVGK-3PHAS/6MODUL



Manufacturer	EATON - MOELLER
MPN / Reference	EVGK-3PHAS/6MODUL
Catalog number	Y7-501075
Category	Phase busbar
Minimum order	20 Pcs
Document ID	EO-137AD63591
Generated	2026-07-29

Product Overview

EVGK-3PHAS/6MODUL

EVGK-3PHAS/6MODUL, EVGK busbar fork, 3-phase, L1 - L2 - L3, shortenable version with end caps included, 6 module units, 10 mm²

Busbar for miniature circuit-breaker, residual-current circuit-breakers, combined residual-current/power circuit-breaker, preinstalled end caps (can also be ordered separately), can be cut to length, RAL 7035 color, halogen free (DIN EN 60754-1), fire class according to V2, testing by VDE (DIN EN 61439-1:2021-10 DIN EN 61439-6:2013-06), PC-ABS isolation material and PP touch protection material, disruptive strength of 36 kV/mm and overvoltage category III

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Moeller series busbar Catalog Number EP-501075 Model Code EVGK-3PHAS/6MODUL EAN 9010653035190 Product Length/Depth 106 mm Product Height 28.5 mm Product Width 15 mm Product Weight 0.036 kg Certifications CE Product specifications

Features Insulated

Can be cut to size Electric connection type Fork Cross section 10 mm² Number of modular spacings 6 Number of phases 3 Pitch dimensions 17.8 mm Rated operating voltage (Ue) - max 415 V Rated surge voltage 4 KV Rated uninterrupted current (Iu) 63 A Rated short-time withstand current (Icw) 0 kA Number of poles Three-pole Color Grey Rated conditional short-circuit current (Iq) 25 kA Suitable for 2 devices

ETIM for EP-501075 Low-voltage industrial controls and switchgear (EC000215)

Feature Name

Feature Value

Number of phases (EF000351)

3

Number of poles (EF001391)

3

Suitable for number of devices (EF007241)

2

Module width (EF007504)

17.8 mm

Cross section (EF000649)

10 mm²

Length (EF001438)

106 mm

Can be cut to size (EF015250)

Yes

Width in number of modular spacings (EF002950)

6

Rated permanent current I_u (EF001389)

63 A

Type of electric connection (EF003961)

Fork

Insulated (EF000019)

Yes

Rated surge voltage (EF002993)

4 kV

Conditioned rated short-circuit current I_q (EF001444)

25 kA

Max. rated operation voltage U_e (EF007357)

415 V

Rated short-time withstand current I_{cw} (EF007050)

0 kA

Suitable for devices with N-conductor (EF007218)

No

Suitable for devices with auxiliary switch (EF007217)

No

Col...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EVGK-3PHAS/6MODUL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.