

INDUSTRIAL COMPONENT DATA

EVMAF332C 9001-22373 EATON ELECTRIC PDU G4 MA 0U 309 32A 3P 24xC13,24xC39

Brand: EATON - MOELLER | Manufacturer Part Number: EVMAF332C



Manufacturer	EATON - MOELLER
MPN / Reference	EVMAF332C
Catalog number	9001-22373
Category	Power distribution unit (PDU)
Minimum order	1 Pcs
Document ID	EO-704CDF45B5
Generated	2026-08-06

Product Overview

PDU G4 MA 0U 309 32A 3P 24xC13,24xC39

Eaton Managed G4 Rack PDU, 0U, 43U, IEC-60309 input, 3m cord, 3ph, 22kW, 32A, 415/240V, 48 outlets (24)C13, (24)C39

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Single-phase UPS up to 11kVA
--------------	--

Additional Product Information

General specifications

Product Name Eaton Rack PDU G4

Catalog Number EVMAF332C

Model Code PDU G4 MA 0U 309 32A 3P 24xC13,24xC39

EAN 3553340696954

Product Length/Depth 1900 mm

Product Height 53 mm

Product Width 52 mm

Product Weight 6.9 kg

Compliances CB

LVD Directive

RoHS Directive

WEEE Directive

Packaging Directive

EMC Directive

Certifications IEC 62368-1

EN IEC 63000

CISPR 35/EN 55035

CE

EAC

UKCA

Cm

Ukr

IEC/EN 61000-6-2

IEC/EN 61000-6-4

IEC 61000-3-11

IEC 61000-3-12

Additional information

Operating Temperature 0° to 60°C (32° to 140°F)

Accessories Rack PDU

Rack mounting accessories

Quickstart guide

Safety Instructions

Material Aluminium

Color Black

Electrical input

Input connection IEC-60309 32A 3Ph

Wattage 22 kW max

Amperage Rating 32 A

Input voltage 240/415V

Phase Three-phase

Frequency rating 50/60 Hz

Cord length 3m

Electrical output

Outlets (24) C13, (24) C39

Number of Outputs C13 24

Number of Outputs C19 24

Number of outputs (other) 24

Number of outlets with earth pin 48

Technology & communications

Type Managed Rack PDU

Outlet control Yes

Special features Remote Site Management

Versatile C39 outlet supports C14 or C20 power cord plug

High retention outlets designed to securely fit standard power cords and support P-Lock power cords

Cybersecurity standards UL 2900-1 and IEC 62443-4-2

Hot-Swap network control module

Network Cascading, connect up to 32 PDUs via network loop

Power sharing between two network modules PDUs ensures constant access to PDU data & sensors

1% IEC....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EVMAF332C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.