

INDUSTRIAL COMPONENT DATA

EWK-03091 174663 EATON ELECTRIC EWK-03091 EWK wall-mount enclosure with standard mounting units, 72 SU, IP43..

Brand: EATON - MOELLER | Manufacturer Part Number: EWK-03091



Manufacturer	EATON - MOELLER
MPN / Reference	EWK-03091
Catalog number	174663
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-92FDD7DF27
Generated	2026-08-06

Product Overview

EWK-03091 EWK wall-mount enclosure with standard mounting units, 72 SU, IP43, IK09, protection class 2, RAL9016, HxWxB=950x300x160mm

EWK wall-mount enclosure including standard mounting units, 72 SU for modular DIN devices, plastic protective shroud, galvanized high-grade steel mounting rails, compact enclosure dimensions, since the depth is only 160 mm, rated operational current max. 160A, for direct mounting on the wall, IP43 degree of protection and IK09 impact resistance as per standard IEC/EN 62208, protection class 2, isolation protection, adjustable hinges for easily changing the door handing, very sturdy, door 1 wing, 1 clip-in, 2 cable entry plate inserts included, including N-terminal: 1x (6x1,5-16mm² + 21x0,75-4mm²) , including PE-terminal: 1x (6x1,5-16mm² + 21x0,75-4mm²), color white RAL9016

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Compact Distribution Boxes
--------------	--

Additional Product Information

EL-Nummer (Norway)2455851EWK wall-mount enclosure with standard mounting units, 72 SU, IP43, IK09, protection class 2, RAL9016, HxWxB=950x300x160mmEWK wall-mount enclosure including standard mounting units, 72 SU for modular DIN devices, plastic protective shroud, galvanized high-grade steel mounting rails, compact enclosure dimensions, since the depth is only 160 mm, rated operational current max. 160A, for direct mounting on the wall, IP43 degree of protection and IK09 impact resistance as per standard IEC/EN 62208, protection class 2, isolation protection, adjustable hinges for easily changing the door handing, very sturdy, door 1 wing, 1 clip-in, 2 cable entry plate inserts included, including

N-terminal: 1x (6x1,5-16mm² + 21x0,75-4mm²), including PE-terminal: 1x (6x1,5-16mm² + 21x0,75-4mm²), color white
RAL9016Delivery program

Basic functionBasic deviceProduct functionInstallation distribution boardsProduct rangeEWK DBODesignSurface
mountedInstallation siteIndoorType of installationSurface mountingDoor/FlapWhiteDegree of
ProtectionIP43ColourWhiteModule rackRail-frameShroud for protection against accidental contactPlasticRows
[Count]6Module units per row12DescriptionIP43

Protection Class II

Steel sheet enclosure white (RAL 9016)Cable entriesCable entries on top and bottom, back platePE and N terminals
designPlug-in terminalsPE and N terminals [Number x cross-sectional area]PE: 6 x (1.5 - 16)

N: 21 x (0.75 - 4) mm²Equipment suppliedEnclosure

Installation panel for modular...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EWK-03091 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.