

INDUSTRIAL COMPONENT DATA

EWK-05061 174656 EATON ELECTRIC EWK-05061 EWK wall-mount enclosure with standard mounting units, 96 SU, IP43..

Brand: EATON - MOELLER | Manufacturer Part Number: EWK-05061



Manufacturer	EATON - MOELLER
MPN / Reference	EWK-05061
Catalog number	174656
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-D816D2A4D0
Generated	2026-08-06

Product Overview

EWK-05061 EWK wall-mount enclosure with standard mounting units, 96 SU, IP43, IK09, protection class 2, RAL9016, HxWxB=650x550x160mm

EWK wall-mount enclosure including standard mounting units, 96 SU for modular DIN devices, plastic protective shroud, galvanized high-grade steel mounting rails, compact enclosure dimensions, since the depth is only 160 mm, rated operational current max. 160A, for direct mounting on the wall, IP43 degree of protection and IK09 impact resistance as per standard IEC/EN 62208, protection class 2, isolation protection, adjustable hinges for easily changing the door handing, very sturdy, door 1 wing, 1 clip-in, 4 cable entry plate inserts included, including N-terminal: 2x (6x1,5-16mm² + 21x0,75-4mm²) , including PE-terminal: 2x (6x1,5-16mm² + 21x0,75-4mm²), color white RAL9016

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Compact Distribution Boxes

Additional Product Information

EWK wall-mount enclosure with standard mounting units, 96 SU, IP43, IK09, protection class 2, RAL9016, HxWxB=650x550x160mm Alternate Catalog No. EWK-05061 EL-Nummer (Norway) 2455844 EWK wall-mount enclosure including standard mounting units, 96 SU for modular DIN devices, plastic protective shroud, galvanized high-grade steel mounting rails, compact enclosure dimensions, since the depth is only 160 mm, rated operational current max. 160A, for direct mounting on the wall, IP43 degree of protection and IK09 impact resistance as per standard IEC/EN 62208, protection class 2, isolation protection, adjustable hinges for easily changing the door handing, very sturdy, door 1 wing, 1

clip-in, 4 cable entry plate inserts included, including N-terminal: 2x (6x1,5-16mm² + 21x0,75-4mm²), including PE-terminal: 2x (6x1,5-16mm² + 21x0,75-4mm²), color white RAL9016 [Delivery program

Basic function Basic device Product function Installation distribution boards Product range EWK DBO Design Surface mounted Installation site Indoor Type of installation Surface mounting Door/Flap White Degree of Protection IP43 Colour White Module rack Rail-frame Shroud for protection against accidental contact Plastic Rows [Count] 4 Module units per row 24 Description IP43

Protection Class II

Steel sheet enclosure white (RAL 9016) Cable entries Cable entries on top and bottom, back plate PE and N terminals design Plug-in terminals PE and N terminals [Number x cross-sectional area] PE: 2 x 6 x (1.5 - 16)

N: 2....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EWK-05061 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.