

INDUSTRIAL COMPONENT DATA

EWP-10082 174675 EATON ELECTRIC EWP-10082 EWP wall-mount enclosure for EP standard mounting units, IP54, pro..

Brand: EATON - MOELLER | Manufacturer Part Number: EWP-10082



Manufacturer	EATON - MOELLER
MPN / Reference	EWP-10082
Catalog number	174675
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-FF846288C8
Generated	2026-08-06

Product Overview

EWP-10082 EWP wall-mount enclosure for EP standard mounting units, IP54, protection class 2, RAL9016, without EP modules, HxWxB=800x1050x225mm

EWP wall-mounting enclosure for EP standard components with a max. rated operational current of 250 A, for mounting on the wall with the enclosed wall mounting brackets, IP54 degree of protection and IK09 impact resistance as per standard IEC/EN 62208, protection class 2, isolation protection, very sturdy, door 2 wings, 3-point locking system, 8 cable entry plate inserts included, color white RAL9016, without EP modules

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

EL-Nummer (Norway)2455863EWP wall-mount enclosure for EP standard mounting units, IP54, protection class 2, RAL9016, without EP modules, HxWxB=800x1050x225mmEWP wall-mounting enclosure for EP standard components with a max. rated operational current of 250 A, for mounting on the wall with the enclosed wall mounting brackets, IP54 degree of protection and IK09 impact resistance as per standard IEC/EN 62208, protection class 2, isolation protection, very sturdy, door 2 wings, 3-point locking system, 8 cable entry plate inserts included, color white RAL9016, without EP modulesDesign verification as per IEC/EN 61439

Technical data for design verificationHeat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890Individual enclosure for wall mounting [PV]93 WHeat dissipation, at an ambient

temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890 Starting enclosure for wall mounting [PV]91 W Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890 Middle enclosure for wall mounting [PV]90 W Heat dissipation, at an ambient temperature of 35°C, delta T: 35 degrees in top of the enclosure, calculated as per IEC 60890 Individual enclosure for wall mounting [PV]186 W Heat dissipation, at an ambient temperature of 35°C, delta T: 35 degrees in top of the enclosure, calculated as per IEC 60890 Starting enclosure for wall mount...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EWP-10082 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.