

INDUSTRIAL COMPONENT DATA

EWP-13082 174676 EATON ELECTRIC EWP-13082 EWP wall-mount enclosure for EP standard mounting units, IP54, pro..

Brand: EATON - MOELLER | Manufacturer Part Number: EWP-13082



Manufacturer	EATON - MOELLER
MPN / Reference	EWP-13082
Catalog number	174676
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-35A2467F69
Generated	2026-08-05

Product Overview

EWP-13082 EWP wall-mount enclosure for EP standard mounting units, IP54, protection class 2, RAL9016, without EP modules, HxWxB=800x1300x225mm

EWP wall-mounting enclosure for EP standard components with a max. rated operational current of 250 A, for mounting on the wall with the enclosed wall mounting brackets, IP54 degree of protection and IK09 impact resistance as per standard IEC/EN 62208, protection class 2, isolation protection, very sturdy, door 2 wings, 3-point locking system, 10 cable entry plate inserts included, color white RAL9016, without EP modules

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

EWP wall-mount enclosure for EP standard mounting units, IP54, protection class 2, RAL9016, without EP modules, HxWxB=800x1300x225mm Alternate Catalog No. EWP-13082 EL-Nummer (Norway) 0002455864 EWP wall-mounting enclosure for EP standard components with a max. rated operational current of 250 A, for mounting on the wall with the enclosed wall mounting brackets, IP54 degree of protection and IK09 impact resistance as per standard IEC/EN 62208, protection class 2, isolation protection, very sturdy, door 2 wings, 3-point locking system, 10 cable entry plate inserts included, color white RAL9016, without EP modules [Design verification as per IEC/EN 61439

Technical data for design verification Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890 Individual enclosure for wall mounting [PV] 125 W Heat dissipation, at an ambient

temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890 Starting enclosure for wall mounting [PV] 121 W Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890 Middle enclosure for wall mounting [PV] 118 W Heat dissipation, at an ambient temperature of 35°C, delta T: 35 degrees in top of the enclosure, calculated as per IEC 60890 Individual enclosure for wall mounting [PV] 251 W Heat dissipation, at an ambient temperature of 35°C, delta T: 35 degrees in top of the enclosure, calcul...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EWP-13082 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.