

INDUSTRIAL COMPONENT DATA

EWS-03062 174622 EATON ELECTRIC EWS-03062 EWS wall-mount enclosure for EP standard mounting units, IP43, IK0..

Brand: EATON - MOELLER | Manufacturer Part Number: EWS-03062



Manufacturer	EATON - MOELLER
MPN / Reference	EWS-03062
Catalog number	174622
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-B430BD4BA6
Generated	2026-08-06

Product Overview

EWS-03062 EWS wall-mount enclosure for EP standard mounting units, IP43, IK09, protection class 2, RAL9016 , without EP modules, HxWxB=650x300x210mm

EWS wall-mounting enclosure for EP standard components with a max. rated operational current of max. 250A, for direct mounting on the wall, IP43 degree of protection and IK09 impact resistance as per standard IEC/EN 62208, protection class 2, isolation protection, adjustable hinges for easily changing the door handing, very sturdy, door 1 wing, 1 clip-in, 2 cable entry plate inserts included, color white RAL9016, without EP modules

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

EL-Nummer (Norway)2455810EWS wall-mount enclosure for EP standard mounting units, IP43, IK09, protection class 2, RAL9016 , without EP modules, HxWxB=650x300x210mmEWS wall-mounting enclosure for EP standard components with a max. rated operational current of max. 250A, for direct mounting on the wall, IP43 degree of protection and IK09 impact resistance as per standard IEC/EN 62208, protection class 2, isolation protection, adjustable hinges for easily changing the door handing, very sturdy, door 1 wing, 1 clip-in, 2 cable entry plate inserts included, color white RAL9016, without EP modulesDesign verification as per IEC/EN 61439

Technical data for design verificationHeat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890Individual enclosure for wall mounting [PV]36 WHeat dissipation, at an ambient

temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890Starting enclosure for wall mounting [PV]33 WHeat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890Middle enclosure for wall mounting [PV]30 WHeat dissipation, at an ambient temperature of 35°C, delta T: 35 degrees in top of the enclosure, calculated as per IEC 60890Individual enclosure for wall mounting [PV]73 WHeat dissipation, at an ambient temperature of 35°C, delta T: 35 degrees in top of the enclosure, calculated as per IEC 60890Starting enclosu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EWS-03062 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.