

INDUSTRIAL COMPONENT DATA

EWS-13092 174635 EATON ELECTRIC EWS-13092 EWS wall-mount enclosure for EP standard mounting units, IP43, IK0..

Brand: EATON - MOELLER | Manufacturer Part Number: EWS-13092



Manufacturer	EATON - MOELLER
MPN / Reference	EWS-13092
Catalog number	174635
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-7FC7904C95
Generated	2026-08-06

Product Overview

EWS-13092 EWS wall-mount enclosure for EP standard mounting units, IP43, IK09, protection class 2, RAL9016 , without EP modules, HxWxB=950x1300x210mm

EWS wall-mounting enclosure for EP standard components with a max. rated operational current of max. 250A, for direct mounting on the wall, IP43 degree of protection and IK09 impact resistance as per standard IEC/EN 62208, protection class 2, isolation protection, adjustable hinges for easily changing the door handing, very sturdy, door 2 wings,3-point locking system, 10 cable entry plate inserts included, color white RAL9016, without EP modules

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

EL-Nummer (Norway)2455823EWS wall-mount enclosure for EP standard mounting units, IP43, IK09, protection class 2, RAL9016 , without EP modules, HxWxB=950x1300x210mmEWS wall-mounting enclosure for EP standard components with a max. rated operational current of max. 250A, for direct mounting on the wall, IP43 degree of protection and IK09 impact resistance as per standard IEC/EN 62208, protection class 2, isolation protection, adjustable hinges for easily changing the door handing, very sturdy, door 2 wings,3-point locking system, 10 cable entry plate inserts included, color white RAL9016, without EP modulesDesign verification as per IEC/EN 61439

Technical data for design verificationHeat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890Individual enclosure for wall mounting [PV]144 WHeat dissipation, at an ambient

temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890 Starting enclosure for wall mounting [PV]143 W Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890 Middle enclosure for wall mounting [PV]143 W Heat dissipation, at an ambient temperature of 35°C, delta T: 35 degrees in top of the enclosure, calculated as per IEC 60890 Individual enclosure for wall mounting [PV]288 W Heat dissipation, at an ambient temperature of 35°C, delta T: 35 degrees in top of the enclosure, calculated as per IEC 60...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EWS-13092 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.