

INDUSTRIAL COMPONENT DATA

DXA-EXT-3DI1RO 169036 Y7-169036 EATON ELECTRIC Expansion for DA1 variable frequency drives (3 DI, 1REL)

Brand: EATON - MOELLER | Manufacturer Part Number: DXA-EXT-3DI1RO



Manufacturer	EATON - MOELLER
MPN / Reference	DXA-EXT-3DI1RO
Catalog number	Y7-169036
Category	Accessories/spare parts for frequency controller
Minimum order	1 Pcs
Document ID	EO-8318C6BB62
Generated	2026-08-02

Product Overview

Expansion for DA1 variable frequency drives (3 DI, 1REL)

DXA-EXT-3DI1RO

I/O expansion, Subrange: I/O expansion, Description: 3 digital inputs (+24 V), 1 relay output (N/O, 250 V AC, max. 6 A/ 30 V DC, max. 5 A), For use with: DA1, Connection technique: Plug-in module with plug-in terminal blocks, 6 pole

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Power XL Frequency Converters

Additional Product Information

General specifications

Product Name Eaton DA1 Accessory I/O expansion Catalog Number 169036 Model Code DXA-EXT-3DI1RO EAN

4015081655298 Product Length/Depth 38 mm Product Height 170 mm Product Width 120 mm Product Weight 0.03 kg

Certifications CSA-C22.2 No. 14

UL File No.: E172143

Certified by UL for use in Canada

UL

IEC/EN61800-3

UL Category Control No.: NMMS, NMMS7

UL report applies to both US and Canada

IEC/EN61800-5

CE

UL 508C General

Accessory/spare part type Extension module Degree of protection IP00 Product Category Accessories Suitable for Branch circuits, (UL/CSA) Climatic environmental conditions

Ambient operating temperature - min -10 °C Ambient operating temperature - max 50 °C Main circuit

Voltage rating - max 250 V Control circuit

Input 3 Digital inputs (24 V) Output 1 Relay Output (N/O, 250 V AC, max. 6 A/ 30 V DC, max. 5 A) Design verification

10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect.

effects Meets the product standard's requirements. 10.2.4 Resistance to ultra-violet (UV) radiation Meets the product standard's requirements. 10.2.5 Lifting Does not apply, since the entire switchgear needs to be evaluated. 10.2.6

Mechanical impact Does not apply,...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DXA-EXT-3DI1RO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.