

INDUSTRIAL COMPONENT DATA

FAZ-B12/1N 278645 Y7-278645 EATON ELECTRIC Small circuit breaker

Brand: EATON - MOELLER | Manufacturer Part Number: FAZ-B12/1N



Manufacturer	EATON - MOELLER
MPN / Reference	FAZ-B12/1N
Catalog number	Y7-278645
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-70D2E6345D
Generated	2026-08-05

Product Overview

Small circuit breaker

Miniature circuit breaker (MCB), 12 A, 1p+N, characteristic: B

Miniature circuit breaker (MCB), FAZ, 1-pole+N, tripping characteristic: B, rated current In: 12 A, Switchgear for industrial and advanced commercial applications

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Industrial

Additional Product Information

Miniature circuit breaker (MCB), 12 A, 1p+N, characteristic: B
Miniature circuit breaker (MCB), FAZ, 1-pole+N, tripping characteristic: B, rated current In: 12 A, Switchgear for industrial and advanced commercial applications

General specifications
Product name Eaton Moeller series xEffect - FAZ MCB

Part no. FAZ-B12/1N
EAN 4015082786458
Product Length/Depth 80 millimetre
Product height 75.5 millimetre
Product width 36 millimetre
Product weight 0.198 kilogram
Compliance RoHS conform
Certifications IEC/EN 60898 IEC/EN 60947-2

EN45545-2

IEC 61373
Product Trade name xEffect - FAZ
Product Type MCB
Product Sub Type None
Delivery

program Application Switchgear for industrial and advanced commercial applications

xEffect - Switchgear for industrial and advanced commercial applications
Number of poles Single-pole + N
Number of poles (total) 2
Number of poles (protected) 1
Tripping characteristic B
Release characteristic BA
Amperage Rating 12 A
Type FAZ

Miniature circuit breaker
Technical Data - Electrical
Voltage type AC
Voltage rating 240 V AC / 415 V AC
Voltage rating at

DC60 V DC (per pole)Voltage rating (IEC/EN 60898-1)240 V ACVoltage rating (UL)277 VRated operational voltage (Ue) - max230 VOperational voltage (IEC/EN 60947-2) - max254 V ACRated insulation voltage (Ui)440 VRated impulse withstand voltage (Uimp)4 kVFrequency rating - min50 HzFrequency rating - max60 HzRated switching capacity (IEC/EN 60947-2) at max voltage rating10 kARated switching capacity (IEC/EN 60947-2)15 kARated switching capacity (IEC/EN 60898-1)10 kAOper...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZ-B12/1N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.