

INDUSTRIAL COMPONENT DATA

FAZ-B20/1N 278649 Y7-278649 EATON ELECTRIC Miniature circuit breaker (MCB), 20A, 1Np, B-Char, AC

Brand: EATON - MOELLER | Manufacturer Part Number: FAZ-B20/1N



Manufacturer	EATON - MOELLER
MPN / Reference	FAZ-B20/1N
Catalog number	Y7-278649
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-5CA44592AF
Generated	2026-08-06

Product Overview

Miniature circuit breaker (MCB), 20A, 1Np, B-Char, AC

Small circuit breaker

Miniature circuit breaker (MCB), 20 A, 1p+N, characteristic: B

Miniature circuit breaker (MCB), FAZ, 1-pole+N, tripping characteristic: B, rated current In: 20 A, Switchgear for industrial and advanced commercial applications

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Industrial
--------------	---

Additional Product Information

Miniature circuit breaker (MCB), 20 A, 1p+N, characteristic: B
Miniature circuit breaker (MCB), FAZ, 1-pole+N, tripping characteristic: B, rated current In: 20 A, Switchgear for industrial and advanced commercial applications

General specifications
Product name Eaton Moeller series xEffect - FAZ MCB
Part no. FAZ-B20/1N

EAN 4015082786496
Product Length/Depth 80 millimetre
Product height 75.5 millimetre
Product width 36 millimetre
Product weight 0.199 kilogram

Compliance RoHS conform

Certifications IEC/EN 60947-2

IEC/EN 60898

IEC 61373

EN 45545-2
Product Trade name xEffect - FAZ
Product Type MCB
Product Sub Type None

Delivery program Application Switchgear for industrial and advanced commercial applications

xEffect - Switchgear for industrial and advanced commercial applications
Number of poles Single-pole + N
Number of poles (total) 4
Number of poles (protected) 4
Tripping characteristic B
Release characteristic C

BAmpereage Rating20 ATypeFAZ

Miniature circuit breakerTechnical Data - ElectricalVoltage typeACVoltage rating240 V AC / 415 V ACVoltage rating at DC60 V DC (per pole)Voltage rating (IEC/EN 60898-1)240 V ACVoltage rating (UL)277 VRated operational voltage (Ue) - max230 VOperational voltage (IEC/EN 60947-2) - max254 V ACRated insulation voltage (Ui)440 VRated impulse withstand voltage (Uimp)4 kVFrequency rating - min50 HzFrequency rating - max60 HzRated switching capacity (IEC/EN 60947-2) at max voltage rating10 kARated switching capacity (IEC/EN 60947-2)15 kARated switching capacity (IEC/EN 60898-1)10 kAOp...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZ-B20/1N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.