

INDUSTRIAL COMPONENT DATA

FAZ-B25/4 279037 Y7-279037 EATON ELECTRIC Miniature circuit breaker (MCB), 25A, 4p, B-Char, AC

Brand: EATON - MOELLER | Manufacturer Part Number: FAZ-B25/4



Manufacturer	EATON - MOELLER
MPN / Reference	FAZ-B25/4
Catalog number	Y7-279037
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-2B6DE7B024
Generated	2026-08-05

Product Overview

Miniature circuit breaker (MCB), 25A, 4p, B-Char, AC

FAZ-B25/4

Eaton Moeller series xEffect - FAZ MCB. FAZ, 4 pole, tripping characteristic: B, rated current In: 25 A

Miniature circuit breaker (MCB), FAZ, 4 pole, tripping characteristic: B, rated current In: 25 A, Switchgear for industrial and advanced commercial applications

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Industrial
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - FAZ MCB Catalog Number 279037 Model Code FAZ-B25/4 EAN

4015082790370 Product Length/Depth 80 mm Product Height 75.5 mm Product Width 72 mm Product Weight 0.464 kg

Compliances RoHS conform Certifications IEC/EN 60898

IEC/EN 60947-2

EN45545-2

IEC 61373 Product specifications

Type Special features Ambient temperature hint: a 1 °C increase results in a 0.5% linear reduction of current carrying capacity Application Switchgear for industrial and advanced commercial applications

xEffect - Switchgear for industrial and advanced commercial applications

Amperage Rating 25 A Voltage rating 240 V AC / 415 V AC Features Concurrently switching N-neutral

Additional equipment possible Frame 45 mm Pollution degree 2 Mounting Method Top-hat rail IEC/EN 60715 Degree of protection IP40 (when fitted)

IP20 Equipment heat dissipation, current-dependent 12 W Rated impulse withstand voltage (Uimp) 4 kV Admissible back-up fuse - max 125 A gL/gG Breaking capacity 10 kA (UL1077) Busbar material thickness 0.8 mm - 2 mm Terminal protection Finger and hand touch safe, DGUV VS3, EN 50274 Terminals (top and bottom) Twin-purpose terminals Tripping characteristic B Ambient operating temperature - max 75 °C Ambient operating temperature - min -25 °C Built-in depth 70.5 mm Connectable conductor cross section (multi-wired) - max 25 mm² Connectable conductor cross section (multi-wired) - min 1 mm² Connectable conductor cross section (solid-core) -...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZ-B25/4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.