

INDUSTRIAL COMPONENT DATA

FAZ-B3/2-NA 132696 Y7-132696 EATON ELECTRIC Miniature circuit breaker (MCB), 3A, 2p, B-Char, AC

Brand: EATON - MOELLER | Manufacturer Part Number: FAZ-B3/2-NA



Manufacturer	EATON - MOELLER
MPN / Reference	FAZ-B3/2-NA
Catalog number	Y7-132696
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-B5BF427F66
Generated	2026-08-04

Product Overview

Miniature circuit breaker (MCB), 3A, 2p, B-Char, AC

FAZ-B3/2-NA

Eaton Moeller series xEffect - FAZ-NA, FAZ-RT MCB. FAZ-NA, 2-pole, tripping characteristic: B, rated current In: 3 A, Switchgear for export to North America (UL-listed)

Miniature circuit breaker (MCB), FAZ-NA, 2-pole, tripping characteristic: B, rated current In: 3 A, Switchgear for export to North America (UL-listed)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Industrial
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - FAZ-NA, FAZ-RT MCB Catalog Number 132696 Model Code FAZ-B3/2-NA
EAN 4015081296453 Product Length/Depth 105 mm Product Height 75.5 mm Product Width 35.4 mm Product Weight
0.246 kg Compliances RoHS conform Certifications UL 489

UL (Category Control Number DIVQ)

CSA (File No. 204453)

CSA (Class No. 1432-01)

IEC 60947-2

CSA-C22.2 No. 5-09

Specially designed for North America, suitable as BCPD

UL 489, CSA C22.2 No. 5

North America (UL listed, CSA certified)

IEC/EN 60947-2

CE marking

UL (File No. E235139)

EN45545-2

IEC 61373 Product specifications

Type Special features Ambient temperature hint: a 1 °C increase results in a 0.5% linear reduction of current carrying capacity Application Feeder circuits, branch circuits

Switchgear for export to North America (UL-listed)

Amperage Rating 3 A Voltage rating 277 V AC / 480 V AC Features Additional equipment possible Frame 45 mm Pollution degree 2 Used with Miniature circuit breaker

FAZ-NA Mounting Method Top-hat rail IEC/EN 60715 Degree of protection IP40 (when fitted)

IP20 (IEC)

UL/CSA Type: -

IP20 Equipment heat dissipation, current-dependent 4.2 W Rated impulse withstand voltage (Uimp) 4 kV Breaking capacity 10 kA (UL489) Terminal protection Finger and hand touch safe, DGUV VS3, EN 50274 Terminals (top and bottom)

Twin-purpose terminals Tripping characteristic B Ambient operating temperature - max 75 °C Ambient operating temperature - min -25 °C Built-in depth 70.5 mm....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZ-B3/2-NA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.