

INDUSTRIAL COMPONENT DATA

FAZ-B35/2-NA 132710 Y7-132710 EATON ELECTRIC Miniature circuit breaker (MCB), 35A, 2p, B-Char, AC

Brand: EATON - MOELLER | Manufacturer Part Number: FAZ-B35/2-NA



Manufacturer	EATON - MOELLER
MPN / Reference	FAZ-B35/2-NA
Catalog number	Y7-132710
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-0D3385A424
Generated	2026-08-06

Product Overview

Miniature circuit breaker (MCB), 35A, 2p, B-Char, AC

FAZ-B35/2-NA

Eaton Moeller series xEffect - FAZ-NA, FAZ-RT MCB. FAZ-NA, 2-pole, tripping characteristic: B, rated current In: 35 A, Switchgear for export to North America (UL-listed)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Industrial

Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - FAZ-NA, FAZ-RT MCB Catalog Number 132710 Model Code FAZ-B35/2-NA

EAN 4015081296590 Product Length/Depth 105 mm Product Height 75.5 mm Product Width 35.4 mm Product Weight

0.254 kg Compliances RoHS conform Certifications CSA-C22.2 No. 5-09

UL (Category Control Number DIVQ)

UL 489, CSA C22.2 No. 5

UL 489

Specially designed for North America, suitable as BCPD

CSA (File No. 204453)

North America (UL listed, CSA certified)

CE marking

CSA (Class No. 1432-01)

UL (File No. E235139)

IEC 60947-2

IEC/EN 60947-2

EN45545-2

IEC 61373 Product specifications

Type Special features Ambient temperature hint: a 1 °C increase results in a 0.5% linear reduction of current carrying capacity Application Feeder circuits, branch circuits

Switchgear for export to North America (UL-listed)

Amperage Rating 35 A Voltage rating 240 V AC Features Additional equipment possible Frame 45 mm Pollution degree 2

Used with Miniature circuit breaker

FAZ-NA Mounting Method Top-hat rail IEC/EN 60715 Degree of protection IP40 (when fitted)

IP20 (IEC)

UL/CSA Type: -

IP20 Equipment heat dissipation, current-dependent 8.1 W Rated impulse withstand voltage (Uimp) 4 kV Breaking capacity 10 kA (UL489) Terminal protection Finger and hand touch safe, DGVV VS3, EN 50274 Terminals (top and bottom)

Twin-purpose terminals Tripping characteristic B Ambient operating temperature - max 75 °C Ambient operating temperature - min -25 °C Built-in depth 70.5 mm Connectab...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZ-B35/2-NA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.