

INDUSTRIAL COMPONENT DATA

FAZ-B4/1-HS 279274 Y7-279274 EATON ELECTRIC Int. circuit breaker FAZ-NA, 4A, 1P, curve B UL

Brand: EATON - MOELLER | Manufacturer Part Number: FAZ-B4/1-HS



Manufacturer	EATON - MOELLER
MPN / Reference	FAZ-B4/1-HS
Catalog number	Y7-279274
Category	Miniature circuit breaker (MCB)
Minimum order	12 Pcs
Document ID	EO-0E7667FCF9
Generated	2026-08-06

Product Overview

Int. circuit breaker FAZ-NA, 4A, 1P, curve B UL

Eaton Moeller series xEffect - FAZ-HS MCB. FAZ-HS, 1-pole, tripping characteristic: B, rated current In: 4 A

Miniature circuit breaker (MCB), FAZ-HS, 1-pole, tripping characteristic: B, rated current In: 4 A, Switchgear for industrial and advanced commercial applications

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Industrial
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - FAZ-HS MCB Catalog Number 279274 Model Code FAZ-B4/1-HS EAN 4015082792749 Product Length/Depth 80 mm Product Height 75.5 mm Product Width 17.7 mm Product Weight 0.112 kg

Compliances RoHS conform Certifications CE marking

IEC/EN 60898

IEC/EN 60947-2 Product specifications

Type Application Branch circuits, not as BCPD

Switchgear for industrial and advanced commercial applications

xEffect - Switchgear for industrial and advanced commercial applications

Amperage Rating 4 A Voltage rating 240 V AC / 415 V AC Features Additional equipment possible Frame 45 mm Pollution degree 2 Used with Miniature circuit breaker

FAZ-HS Mounting Method Top-hat rail IEC/EN 60715 Degree of protection IP40 (when fitted)

IP20 (IEC)

UL/CSA Type: -

IP20 Rated impulse withstand voltage (Uimp) 4 kV Admissible back-up fuse - max 125 A gL/gG Busbar material thickness 0.8 mm - 2 mm Terminal protection Finger and hand touch safe, DGUV VS3, EN 50274 Terminals (top and bottom) Twin-purpose terminals Tripping characteristic B Voltage rating (UL CSA 13) 277 V AC; 48 V DC Ambient operating temperature - max 75 °C Ambient operating temperature - min -25 °C Built-in depth 70.5 mm Connectable conductor cross section (multi-wired) - max 25 mm² Connectable conductor cross section (multi-wired) - min 1 mm² Connectable conductor cross section (solid-core) - max 25 mm² Connectable conductor cross section (solid-core) - min 1 mm² Current limiting class 3 En...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZ-B4/1-HS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.