

INDUSTRIAL COMPONENT DATA

FAZ-B5/4-RT 190849 Y7-190849 EATON ELECTRIC Int. circuit breaker FAZ-RT, 5A, 4P, curve B

Brand: EATON - MOELLER | Manufacturer Part Number: FAZ-B5/4-RT



Manufacturer	EATON - MOELLER
MPN / Reference	FAZ-B5/4-RT
Catalog number	Y7-190849
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-7EA541819A
Generated	2026-08-06

Product Overview

Int. circuit breaker FAZ-RT, 5A, 4P, curve B

FAZ-B5/4-RT

Eaton Moeller series xEffect - FAZ-NA, FAZ-RT MCB. Miniature circuit breaker (MCB), 5 A, 4p, characteristic: B, ring tongue

High-quality miniature circuit breaker, according to UL 489, CSA C22.2 No. 5 and also IEC 60947-2 standard, for applications, which are permitted for UL 1077 or CSA C22.2 No. 235, auxiliary switch and voltage trips suitable for subsequent installation, with removable terminal screws for use with ring cable lug, contact position indicator red - green, easy mounting at DIN-rail

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Industrial
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - FAZ-NA, FAZ-RT MCB Catalog Number 190849 Model Code FAZ-B5/4-RT

EAN 4015081904969 Product Length/Depth 105 mm Product Height 75.5 mm Product Width 70.8 mm Product Weight 0.49 kg Compliances RoHS conform Certifications CSA (File No. 204453)

Specially designed for North America, suitable as BCPD

IEC 60947-2

CSA-C22.2 No. 5-09

CSA (Class No. 1432-01)

CE marking

UL (File No. E235139)

UL 489

North America (UL listed, CSA certified)

IEC/EN 60947-2

UL (Category Control Number DIVQ)

UL 489, CSA C22.2 No. 5

EN45545-2

IEC 61373 Product specifications

Type Special features Ambient temperature hint: a 1 °C increase results in a 0.5% linear reduction of current carrying capacity

Tripping signal contact for subsequent installation Z-NHK 248434

Application Feeder circuits, branch circuits

Switchgear for export to North America (UL-listed)

xEffect - Switchgear for industrial and advanced commercial applications

Amperage Rating 5 A Voltage rating 277 V AC / 480 V AC Features Additional equipment possible Accessories required

Z-IHK-NA 113895 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.13 Mechanical function The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. 10.2.2 C...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZ-B5/4-RT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.