

INDUSTRIAL COMPONENT DATA

FAZ-B6/2 278728 Y7-278728 EATON ELECTRIC Miniature circuit breaker (MCB), 6A, 2p, B-Char, AC

Brand: EATON - MOELLER | Manufacturer Part Number: FAZ-B6/2



Manufacturer	EATON - MOELLER
MPN / Reference	FAZ-B6/2
Catalog number	Y7-278728
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-79EB2A3969
Generated	2026-08-04

Product Overview

Miniature circuit breaker (MCB), 6A, 2p, B-Char, AC

FAZ-B6/2

Eaton Moeller series xEffect - FAZ MCB. FAZ, 2-pole, tripping characteristic: B, rated current In: 6 A

Miniature circuit breaker (MCB), FAZ, 2-pole, tripping characteristic: B, rated current In: 6 A, Switchgear for industrial and advanced commercial applications

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Industrial

Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - FAZ MCB Catalog Number 278728 Model Code FAZ-B6/2 EAN

4015082787288 Product Length/Depth 80 mm Product Height 75.5 mm Product Width 36 mm Product Weight 0.219 kg

Compliances UL CSA09 (with supplementary protector only)

RoHS conform Certifications CSA-C22.2 No. 235

UL 1077

CSA (File No. 204453)

UL (Category Control Number QVNU2, QVNU8)

North America (UL recognized, CSA certified)

CE marking

UL (File No. E177451)

IEC/EN 60947-2

IEC/EN 60898

CSA (Class No. 3215-30)

EN45545-2

IEC 61373 Delivery Programme

Application Number of poles Two-pole Number of poles (total) 2 Number of poles (protected) 2 Tripping characteristic B

Release characteristic B Amperage Rating 6 A Type FAZ

Miniature circuit breaker

Technical data - electrical

Voltage type AC Voltage rating 240 V AC / 415 V AC Voltage rating at DC 60 V DC (per pole) Voltage rating (IEC/EN 60898-1) 415 VAC Voltage rating (UL) 480Y/277 V Voltage rating (UL CSA 13) 480 Y/277 V AC; 96 V DC Rated operational voltage (Ue) - max 400 V Operational voltage (IEC/EN 60947-2) - max 440 VAC Rated insulation voltage (Ui) 440 V Rated impulse withstand voltage (Uimp) 4 kV Frequency rating - min 50 Hz Frequency rating - max 60 Hz Rated switching capacity (IEC/EN 60947-2) at max voltage rating 10 kA Rated switching capacity (IEC/EN 60947-2) 15 kA Rated switching capacity (IEC/EN 60898-1) 10 kA Operational switching capacity 7.5 kA Breaking capacity 10 kA (UL1077) Rated service sho...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZ-B6/2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.