

INDUSTRIAL COMPONENT DATA

FAZ-B7/3 167493 Y7-167493 EATON ELECTRIC Small circuit breaker

Brand: EATON - MOELLER | Manufacturer Part Number: FAZ-B7/3



Manufacturer	EATON - MOELLER
MPN / Reference	FAZ-B7/3
Catalog number	Y7-167493
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-E2941CB859
Generated	2026-08-04

Product Overview

Small circuit breaker

Miniature circuit breaker (MCB), 7 A, 3p, characteristic: B

Miniature circuit breaker (MCB), FAZ, 3-pole, tripping characteristic: B, rated current I_n : 7 A, rated switching capacity (IEC/EN 60947-2): 15 kA, Switchgear for industrial and advanced commercial applications

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Industrial

Additional Product Information

Miniature circuit breaker (MCB), 7 A, 3p, characteristic: B
Miniature circuit breaker (MCB), FAZ, 3-pole, tripping characteristic: B, rated current I_n : 7 A, rated switching capacity (IEC/EN 60947-2): 15 kA, Switchgear for industrial and advanced commercial applications

General specifications
Product name Eaton Moeller series xEffect - FAZ MCB
Part no. FAZ-B7/3
EAN 4015081639939
Product Length/Depth 80 millimetre
Product height 75.5 millimetre
Product width 54 millimetre
Product weight 0.333 kilogram
Compliances RoHS conform
Certifications EN45545-2

IEC 61373
Product Tradename xEffect - FAZ
Product Type MCB
Product Sub Type None
Delivery program Application Switchgear for industrial and advanced commercial applications

xEffect - Switchgear for industrial and advanced commercial applications
Number of poles Three-pole
Number of poles (total) 3
Number of poles (protected) 3
Tripping characteristic B
Release characteristic B
Amperage Rating 7 A
Type FAZ

Miniature circuit breaker
Technical Data - Electrical
Voltage type AC
Voltage rating (IEC/EN 60898-1) 415 V AC
Rated operational voltage (U_e) - max 415 V
Operational voltage (IEC/EN 60947-2) - max 440 V AC
Rated insulation voltage (U_i) 440

VRated impulse withstand voltage (Uimp)4 kVFrequency rating - min50 HzFrequency rating - max60 HzRated switching capacity (IEC/EN 60947-2) at max voltage rating10 kARated switching capacity (IEC/EN 60947-2)15 kARated switching capacity (IEC/EN 60898-1)10 kARated service short-circuit breaking capacity (IEC/EN 60898-1)7.5 kARated service short-cir...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZ-B7/3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.