

INDUSTRIAL COMPONENT DATA

FAZ-C10/2-RT-DC 305901 Y7-305901 EATON ELECTRIC Int. circuit breaker FAZ, 10A, 2P, curve C, for DC terminal ..

Brand: EATON - MOELLER | Manufacturer Part Number: FAZ-C10/2-RT-DC



Manufacturer	EATON - MOELLER
MPN / Reference	FAZ-C10/2-RT-DC
Catalog number	Y7-305901
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-E2393E5EEA
Generated	2026-08-05

Product Overview

Int. circuit breaker FAZ, 10A, 2P, curve C, for DC terminal ring

Miniature circuit breaker (MCB), 10 A, 2p, characteristic: C, DC, ring tongue

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog pathEATON - MOELLER > Modular Switchgear - Industrial

Additional Product Information

Miniature circuit breaker (MCB), 10 A, 2p, characteristic: C, DC, ring tongue

General specificationsProduct nameEaton Moeller series xEffect - FAZ-DC MCBPart

no.FAZ-C10/2-RT-DCEAN9010238216990Product Length/Depth105 millimetreProduct height75.5 millimetreProduct width35.4 millimetreProduct weight0.247 kilogramCompliancesRoHS conformCertificationsEN45545-2

IEC 61373Product TradenamexEffect - FAZ-DCProduct TypeMCBProduct Sub TypeNoneDelivery programNumber of polesTwo-poleNumber of poles (total)2Number of poles (protected)2Tripping characteristicCRelease characteristicCAmpereage Rating10 ATypeFAZ-DC

Miniature circuit breakerTechnical Data - ElectricalVoltage typeDCRated operational voltage (Ue) - max500 VRated insulation voltage (Ui)440 VRated impulse withstand voltage (Uimp)4 kVFrequency rating - min50 HzFrequency rating - max60 HzRated switching capacity (IEC/EN 60947-2)10 kARated short-circuit breaking capacity (EN 60898) at 230 V0 kARated short-circuit breaking capacity (EN 60898) at 400 V0 kARated short-circuit breaking capacity (IEC 60947-2) at 230 V10 kARated short-circuit breaking capacity (IEC 60947-2) at 400 V10 kASelectivity class3Lifespan, electrical4000 operationsOvervoltage categoryIIIPollution degree2Technical Data - MechanicalFrame45 mmWidth in number of modular spacings2Built-in depth75.5 mmMounting width36 mmMounting width per pole17.7 mmMounting positionAs requiredDegree

of protectionIP20Terminals (top and bottom)Lift terminalsConnectable conductor cross secti...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZ-C10/2-RT-DC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.