

INDUSTRIAL COMPONENT DATA

FAZ-C40/1-NA-DC 113768 Y7-113768 EATON ELECTRIC

FAZ-C40/1-NA-DC Over current switch, 40A, 1p, C-Char, DC cur..

Brand: EATON - MOELLER | Manufacturer Part Number: FAZ-C40/1-NA-DC



Manufacturer	EATON - MOELLER
MPN / Reference	FAZ-C40/1-NA-DC
Catalog number	Y7-113768
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-67DA9C2BE2
Generated	2026-08-04

Product Overview

FAZ-C40/1-NA-DC Over current switch, 40A, 1p, C-Char, DC current

FAZ-C40/1-NA-DC

Miniature circuit breaker (MCB), 40 A, 1p, characteristic: C, DC

Miniature circuit breaker (MCB), FAZ-DC, 1-pole, tripping characteristic: C, rated current In: 40 A, Switchgear for export to North America (UL-listed)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog pathEATON - MOELLER > Modular Switchgear - Industrial

Additional Product Information

Miniature circuit breaker (MCB), 40 A, 1p, characteristic: C, DCMiniature circuit breaker (MCB), FAZ-DC, 1-pole, tripping characteristic: C, rated current In: 40 A, Switchgear for export to North America (UL-listed)

General specificationsProduct nameEaton Moeller series xEffect - FAZ-NA-DC MCBPart

no.FAZ-C40/1-NA-DCEAN4015081133031Product Length/Depth105 millimetreProduct height75.5 millimetreProduct width17.7 millimetreProduct weight0.127 kilogramCompliancesRoHS conformCertificationsUL 489, CSA C22.2 No. 5 IEC 60947-2

IEC 61373

EN45545-2Product TradenamexEffect - FAZ-NA-DCProduct TypeMCBProduct Sub TypeNoneDelivery

programApplicationSwitchgear for export to North America (UL-listed)Number of polesSingle-poleNumber of poles

(total)1Number of poles (protected)1Tripping characteristicCRelease characteristicCAmperage Rating40 ATypeFAZ-DC
Miniature circuit breakerTechnical Data - ElectricalVoltage typeDCVoltage rating at DC250 V DCRated operational voltage
(Ue) - max250 VRated insulation voltage (Ui)440 VRated impulse withstand voltage (Uimp)4 kVFrequency rating - min50
HzFrequency rating - max60 HzRated switching capacity (IEC/EN 60947-2)10 kARated short-circuit breaking capacity (EN
60898) at 230 V0 kARated short-circuit breaking capacity (EN 60898) at 400 V0 kARated short-circuit breaking capacity
(IEC 60947-2) at 230 V10 kARated short-circuit breaking capacity (IEC 60947-2) at 400 V10 kAOvertoltage
categoryIIIPollution degree2Technical Data - MechanicalWidth in number of mod...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZ-C40/1-NA-DC with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.