

INDUSTRIAL COMPONENT DATA

FAZ-D13/4-NA 190835 Y7-190835 EATON ELECTRIC Miniature circuit breaker (MCB), D13, 4 poles, NA

Brand: EATON - MOELLER | Manufacturer Part Number: FAZ-D13/4-NA



Manufacturer	EATON - MOELLER
MPN / Reference	FAZ-D13/4-NA
Catalog number	Y7-190835
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-DE7D648F15
Generated	2026-08-06

Product Overview

Miniature circuit breaker (MCB), D13, 4 poles, NA

FAZ-D13/4-NA

Eaton Moeller series xEffect - FAZ-NA, FAZ-RT MCB. Miniature circuit breaker (MCB), 13 A, 4p, characteristic: D, NA High-quality miniature circuit breaker, according to UL 489, CSA C22.2 No. 5 and also IEC 60947-2 standard, for applications, which are permitted for UL 1077 or CSA C22.2 No. 235, auxiliary switch and voltage trips suitable for subsequent installation, contact position indicator red - green, easy mounting at DIN-rail, Switchgear for North America

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Industrial
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - FAZ-NA, FAZ-RT MCB Catalog Number 190835 Model Code FAZ-D13/4-NA EAN 4015081904822 Product Length/Depth 105 mm Product Height 75.5 mm Product Width 70.8 mm Product Weight 0.483 kg Compliances RoHS conform Certifications Specially designed for North America, suitable as BCPD

IEC 60947-2

CSA-C22.2 No. 5-09

UL (File No. E235139)

CE marking

North America (UL listed, CSA certified)

UL (Category Control Number DIVQ)

CSA (File No. 204453)

IEC/EN 60947-2

CSA (Class No. 1432-01)

UL 489, CSA C22.2 No. 5

UL 489

EN45545-2

IEC 61373 Delivery program

Application Number of poles Four-pole Number of poles (total) 4 Number of poles (protected) 4 Tripping characteristic D

Release characteristic D Amperage Rating 13 A Type FAZ-NA

Miniature circuit breaker

Technical data - electrical

Voltage type AC Voltage rating 277 V AC / 480 V AC Voltage rating at DC 60 V DC Voltage rating (IEC/EN 60947-2) 415 V

Voltage rating (UL) 480Y/277 V Rated operational voltage (Ue) - max 240 V Rated insulation voltage (Ui) 440 V Rated

impulse withstand voltage (Uimp) 4 kV Frequency rating - min 50 Hz Frequency rating - max 60 Hz Rated switching

capacity (IEC/EN 60947-2) 15 kA Operational switching capacity 7.5 kA Rated short-circuit breaking capacity (EN 60898) at

230 V 10 kA Rated short-circuit breaking capacity (EN 60898) at 400 V 15 kA Rated short-circuit breaking capacity (IEC

60947-2) at 230 V 10 kA Rated short-circuit breaking capacity (IEC 609...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZ-D13/4-NA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.