

INDUSTRIAL COMPONENT DATA

FAZ-D2/4-RT 190886 Y7-190886 EATON ELECTRIC Int. circuit breaker FAZ-RT, 2A, 4P, D curve

Brand: EATON - MOELLER | Manufacturer Part Number: FAZ-D2/4-RT



Manufacturer	EATON - MOELLER
MPN / Reference	FAZ-D2/4-RT
Catalog number	Y7-190886
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-2F5E0614ED
Generated	2026-08-04

Product Overview

Int. circuit breaker FAZ-RT, 2A, 4P, D curve

FAZ-D2/4-RT

Eaton Moeller series xEffect - FAZ-NA, FAZ-RT MCB. Miniature circuit breaker (MCB), 2 A, 4p, characteristic: D, ring tongue

High-quality miniature circuit breaker, according to UL 489, CSA C22.2 No. 5 and also IEC 60947-2 standard, for applications, which are permitted for UL 1077 or CSA C22.2 No. 235, auxiliary switch and voltage trips suitable for subsequent installation, with removable terminal screws for use with ring cable lug, contact position indicator red - green, easy mounting at DIN-rail

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Industrial
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - FAZ-NA, FAZ-RT MCB Catalog Number 190886 Model Code FAZ-D2/4-RT
EAN 4015081905331 Product Length/Depth 105 mm Product Height 75.5 mm Product Width 70.8 mm Product Weight
0.498 kg Compliances RoHS conform Certifications UL 489, CSA C22.2 No. 5

IEC 60947-2

North America (UL listed, CSA certified)

UL (File No. E235139)

Specially designed for North America, suitable as BCPD

CE marking

CSA (Class No. 1432-01)

IEC/EN 60947-2

UL 489

UL (Category Control Number DIVQ)

CSA (File No. 204453)

CSA-C22.2 No. 5-09

EN45545-2

IEC 61373 Delivery program

Application Number of poles Four-pole Number of poles (total) 4 Number of poles (protected) 4 Tripping characteristic D

Release characteristic D Amperage Rating 2 A Type FAZ-RT

Miniature circuit breaker

Technical data - electrical

Voltage type AC Voltage rating 277 V AC / 480 V AC Voltage rating at DC 60 V DC Voltage rating (IEC/EN 60947-2) 415 V

Voltage rating (UL) 480Y/277 V Rated operational voltage (Ue) - max 240 V Rated insulation voltage (Ui) 440 V Rated

impulse withstand voltage (Uimp) 4 kV Frequency rating - min 50 Hz Frequency rating - max 60 Hz Rated switching

capacity (IEC/EN 60947-2) 15 kA Operational switching capacity 7.5 kA Rated short-circuit breaking capacity (EN 60898) at

230 V 10 kA Rated short-circuit breaking capacity (EN 60898) at 400 V 15 kA Rated short-circuit breaking capacity (IEC

60947-2) at 230 V 10 kA Rated short-circuit breaking capacity (IEC 60947...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZ-D2/4-RT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.