

INDUSTRIAL COMPONENT DATA

FAZ-D3/2 278773 Y7-278773 EATON ELECTRIC Miniature circuit breaker (MCB), 3A, 2p, type D characteristic

Brand: EATON - MOELLER | Manufacturer Part Number: FAZ-D3/2



Manufacturer	EATON - MOELLER
MPN / Reference	FAZ-D3/2
Catalog number	Y7-278773
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-F906A15FB7
Generated	2026-08-01

Product Overview

Miniature circuit breaker (MCB), 3A, 2p, type D characteristic

FAZ-D3/2

Eaton Moeller series xEffect - FAZ MCB. FAZ, 2-pole, tripping characteristic: D, rated current In: 3 A

Miniature circuit breaker (MCB), FAZ, 2-pole, tripping characteristic: D, rated current In: 3 A, Switchgear for industrial and advanced commercial applications

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Industrial
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - FAZ MCB Catalog Number 278773 Model Code FAZ-D3/2 EAN

4015082787738 Product Length/Depth 80 mm Product Height 75.5 mm Product Width 36 mm Product Weight 0.225 kg

Compliances UL CSA09 (with supplementary protector only)

RoHS conform Certifications UL (Category Control Number QVNU2, QVNU8)

CSA (Class No. 3215-30)

UL 1077

CSA (File No. 204453)

UL (File No. E177451)

IEC/EN 60947-2

North America (UL recognized, CSA certified)

IEC/EN 60898

CE marking

CSA-C22.2 No. 235

EN45545-2

IEC 61373 Delivery Programme

Application Number of poles Two-pole Number of poles (total) 2 Number of poles (protected) 2 Tripping characteristic D

Release characteristic D Amperage Rating 3 A Type FAZ

Miniature circuit breaker

Technical data - electrical

Voltage type AC Voltage rating 240 V AC / 415 V AC Voltage rating (UL CSA 13) 480 Y/277 V AC; 96 V DC Rated

operational voltage (Ue) - max 400 V Rated insulation voltage (Ui) 440 V Rated impulse withstand voltage (Uimp) 4 kV

Frequency rating - min 50 Hz Frequency rating - max 60 Hz Rated switching capacity (IEC/EN 60947-2) 15 kA Rated

short-circuit breaking capacity (EN 60898) at 230 V 10 kA Rated short-circuit breaking capacity (EN 60898) at 400 V 10 kA

Rated short-circuit breaking capacity (IEC 60947-2) at 230 V 15 kA Rated short-circuit breaking capacity (IEC 60947-2) at

400 V 15 kA Overvoltage category III Pollution degree 2 Technical data - mechanical

Width in number of modular spacing...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZ-D3/2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.