

## INDUSTRIAL COMPONENT DATA

**FAZ-D3,5/3 278887 Y7-278887 EATON ELECTRIC Miniature circuit breaker (MCB), 3, 5A, 3p, D-Char, AC**

Brand: EATON - MOELLER | Manufacturer Part Number: FAZ-D3,5/3



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | EATON - MOELLER                 |
| MPN / Reference | FAZ-D3,5/3                      |
| Catalog number  | Y7-278887                       |
| Category        | Miniature circuit breaker (MCB) |
| Minimum order   | 1 Pcs                           |
| Document ID     | EO-1B71A3D16B                   |
| Generated       | 2026-08-06                      |

**Product Overview**

Miniature circuit breaker (MCB), 3, 5A, 3p, D-Char, AC

FAZ-D3,5/3

Eaton Moeller series xEffect - FAZ MCB. FAZ, 3-pole, tripping characteristic: D, rated current In: 3.5 A

Miniature circuit breaker (MCB), FAZ, 3-pole, tripping characteristic: D, rated current In: 3.5 A, Switchgear for industrial and advanced commercial applications

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

Catalog path EATON - MOELLER &gt; Modular Switchgear - Industrial

**Additional Product Information**

General specifications

Product Name Eaton Moeller series xEffect - FAZ MCB Catalog Number 278887 Model Code FAZ-D3,5/3 EAN

4015082788872 Product Length/Depth 80 mm Product Height 75.5 mm Product Width 54 mm Product Weight 0.338 kg

Compliances UL CSA09 (with supplementary protector only)

RoHS conform Certifications UL 1077

CE marking

CSA (Class No. 3215-30)

UL (Category Control Number QVNU2, QVNU8)

UL (File No. E177451)

CSA-C22.2 No. 235

IEC/EN 60947-2

IEC/EN 60898

CSA (File No. 204453)

North America (UL recognized, CSA certified)

EN45545-2

IEC 61373 Delivery Programme

Application Number of poles Three-pole Number of poles (total) 3 Number of poles (protected) 3 Tripping characteristic D

Release characteristic D Amperage Rating 3.5 A Type FAZ

Miniature circuit breaker

Technical data - electrical

Voltage type AC Voltage rating 240 V AC / 415 V AC Voltage rating (UL CSA 13) 480 Y/277 V AC Rated operational voltage (Ue) - max 400 V Rated insulation voltage (Ui) 440 V Rated impulse withstand voltage (Uimp) 4 kV Frequency rating - min 50 Hz Frequency rating - max 60 Hz Rated switching capacity (IEC/EN 60947-2) 15 kA Rated short-circuit breaking capacity (EN 60898) at 230 V 10 kA Rated short-circuit breaking capacity (EN 60898) at 400 V 10 kA Rated short-circuit breaking capacity (IEC 60947-2) at 230 V 15 kA Rated short-circuit breaking capacity (IEC 60947-2) at 400 V 15 kA Overvoltage category III Pollution degree 2 Technical data - mechanical

Width in number of modular spacings 3...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZ-D3,5/3 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.