

INDUSTRIAL COMPONENT DATA

FAZ-D5/2-RT 102223 Y7-102223 EATON ELECTRIC Int. circuit breaker FAZ-RT, 5A, 2P, D curve

Brand: EATON - MOELLER | Manufacturer Part Number: FAZ-D5/2-RT



Manufacturer	EATON - MOELLER
MPN / Reference	FAZ-D5/2-RT
Catalog number	Y7-102223
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-E7D69CABE5
Generated	2026-08-06

Product Overview

Int. circuit breaker FAZ-RT, 5A, 2P, D curve

FAZ-D5/2-RT

Eaton Moeller series xEffect - FAZ-NA, FAZ-RT MCB. FAZ-RT, 2-pole, tripping characteristic: D, rated current In: 5 A

Miniature circuit breaker (MCB), FAZ-RT, 2-pole, tripping characteristic: D, rated current In: 5 A, Switchgear for industrial and advanced commercial applications

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Industrial

Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - FAZ-NA, FAZ-RT MCB Catalog Number 102223 Model Code FAZ-D5/2-RT

EAN 4015081020997 Product Length/Depth 105 mm Product Height 75.5 mm Product Width 35.4 mm Product Weight

0.248 kg Compliances RoHS conform Certifications CSA Std. C22.2 No.235

IEC 60947-2

UL 1077

CSA (File No. 204453)

IEC/EN 60947-2

CSA (Class No. 1432-01)

UL (File No. E235139)

CE marking

Specially designed for North America, suitable as BCPD

UL 489

UL (Category Control Number DIVQ)

North America (UL listed, CSA certified)

UL 489, CSA C22.2 No. 5

CSA-C22.2 No. 5-09

EN45545-2

IEC 61373 Catalog Notes Magnetic range for higher startup inrush levels that are usually seen in motors and transformers, and other high inductive systems. Delivery program

Application Number of poles Two-pole Number of poles (total) 2 Number of poles (protected) 2 Tripping characteristic D

Release characteristic D Amperage Rating 5 A Type FAZ-RT

Miniature circuit breaker

Technical data - electrical

Voltage type AC Voltage rating 277 V AC / 480 V AC Voltage rating at DC 60 V DC Voltage rating (IEC/EN 60947-2) 415 V

Voltage rating (UL) 480Y/277 V Rated operational voltage (Ue) - max 415 V Rated insulation voltage (Ui) 440 V Rated

impulse withstand voltage (Uimp) 4 kV Frequency rating - min 50 Hz Frequency rating - max 60 Hz Rated switching capacity (IEC/EN 60947-2) 15 kA Rated short-circuit breaking capacity (EN 60898) at 230 V 0 kA Rated short-circuit breaking capacity (EN 6...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZ-D5/2-RT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.