

INDUSTRIAL COMPONENT DATA

FAZ-K20/3N 279014 Y7-279014 EATON ELECTRIC Miniature circuit breaker (MCB), 20A, 3Np, K-Char, AC

Brand: EATON - MOELLER | Manufacturer Part Number: FAZ-K20/3N



Manufacturer	EATON - MOELLER
MPN / Reference	FAZ-K20/3N
Catalog number	Y7-279014
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-385065C136
Generated	2026-08-05

Product Overview

Miniature circuit breaker (MCB), 20A, 3Np, K-Char, AC

FAZ-K20/3N

Eaton Moeller series xEffect - FAZ MCB. Miniature circuit breaker (MCB), 20 A, 3p+N, characteristic: K

Miniature circuit breaker (MCB), FAZ, 3-pole+N, tripping characteristic: K, rated current In: 20 A, Switchgear for industrial and advanced commercial applications

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Industrial

Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - FAZ MCB Catalog Number 279014 Model Code FAZ-K20/3N EAN

4015082790141 Product Length/Depth 80 mm Product Height 75.5 mm Product Width 72 mm Product Weight 0.424 kg

Compliances RoHS conform Certifications IEC/EN 60947-2

IEC/EN 60898

EN45545-2

IEC 61373 Delivery Programme

Application Number of poles Three-pole + N Number of poles (total) 2 Number of poles (protected) 1 Tripping characteristic

K Release characteristic K

B Amperage Rating 20 A Type FAZ

Miniature circuit breaker

Technical data - electrical

Voltage type AC Voltage rating 240 V AC / 415 V AC Voltage rating at DC 60 V DC (per pole) Rated operational voltage (Ue) - max 230 V Rated insulation voltage (Ui) 440 V Rated impulse withstand voltage (Uimp) 4 kV Frequency rating - min 50 Hz Frequency rating - max 60 Hz Rated switching capacity (IEC/EN 60947-2) 10 kA Operational switching capacity 7.5 kA Rated short-circuit breaking capacity (EN 60898) at 230 V 4.5 kA Rated short-circuit breaking capacity (EN 60898) at 400 V 4.5 kA Rated short-circuit breaking capacity (IEC 60947-2) at 230 V 0 kA Rated short-circuit breaking capacity (IEC 60947-2) at 400 V 0 kA Admissible back-up fuse - max 125 A gL/gG Selectivity class 3 Overvoltage category III Pollution degree 2 Lifespan, electrical 10000 operations Direction of incoming supply As required Technical data - mechanical Frame 45 mm Enclosure width 80 mm Width in number of modular spacings 1 Built-in depth 70.5....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZ-K20/3N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.