

INDUSTRIAL COMPONENT DATA

FAZ-K40/3-NA EP-501485 Y7-501485 EATON ELECTRIC Miniature circuit breaker (MCB), 40A, 3p, characteristic: K

Brand: EATON - MOELLER | Manufacturer Part Number: FAZ-K40/3-NA



Manufacturer	EATON - MOELLER
MPN / Reference	FAZ-K40/3-NA
Catalog number	Y7-501485
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-1A28AFCA58
Generated	2026-08-06

Product Overview

Miniature circuit breaker (MCB), 40A, 3p, characteristic: K

FAZ-K40/3-NA . Miniature circuit breaker (MCB), 40A, 3p, characteristic: K

Miniature circuit breaker (MCB), FAZ-NA, 3-pole, tripping characteristic: K, rated current In: 40 A, Switchgear for industrial and advanced commercial applications

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Industrial
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - FAZ-NA, FAZ-RT MCB Catalog Number EP-501485 Model Code

FAZ-K40/3-NA EAN 9010653052784 Product Length/Depth 105 mm Product Height 75.5 mm Product Width 53.1 mm

Product Weight 0.382 kg Certifications UL 489, CSA C22.2 No. 5

IEC 60947-2 Product specifications

Type Application Switchgear for export to North America (UL-listed) Amperage Rating 40 A Features Additional equipment possible Frame 45 mm Pollution degree 2 Mounting Method IEC/EN 60715 top-hat rail Degree of protection IP20 IP40 Equipment heat dissipation, current-dependent 9.3 W Rated impulse withstand voltage (Uimp) 4 kV Breaking capacity 14 kA (UL489) Terminal protection Finger and back-of-hand proof to BGV A2 Terminals (top and bottom) Twin-purpose terminals Tripping characteristic B, C, D Ambient operating temperature - max 75 °C Ambient operating temperature - min -25 °C Built-in depth 70.5 mm Connectable conductor cross section (multi-wired) - max 25 mm² Connectable conductor cross section (multi-wired) - min 1 mm² Connectable conductor cross section (solid-core) - max 25 mm² Connectable

conductor cross section (solid-core) - min 1 mm² Current limiting class 3 Frequency rating - max 60 Hz Frequency rating - min 50 Hz Width in number of modular spacings 3 Voltage rating (IEC/EN 60947-2) 440 V Voltage rating (UL) 480Y/277 V AC Voltage rating at DC 60 V DC Voltage type AC Overvoltage category III Lifespan, electrical 20000 operations Release characte...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZ-K40/3-NA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.