

INDUSTRIAL COMPONENT DATA

FAZ-K50/4 279104 Y7-279104 EATON ELECTRIC Miniature circuit breaker (MCB), 50A, 4p, K-Char, AC

Brand: EATON - MOELLER | Manufacturer Part Number: FAZ-K50/4



Manufacturer	EATON - MOELLER
MPN / Reference	FAZ-K50/4
Catalog number	Y7-279104
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-AB0A98BD22
Generated	2026-08-06

Product Overview

Miniature circuit breaker (MCB), 50A, 4p, K-Char, AC

FAZ-K50/4

Miniature circuit breaker (MCB), 50 A, 4p, characteristic: K

Miniature circuit breaker (MCB), FAZ, 4 pole, tripping characteristic: K, rated current In: 50 A, Switchgear for industrial and advanced commercial applications

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Industrial

Additional Product Information

Miniature circuit breaker (MCB), 50 A, 4p, characteristic: KMiniature circuit breaker (MCB), FAZ, 4 pole, tripping characteristic: K, rated current In: 50 A, Switchgear for industrial and advanced commercial applications

General specificationsProduct nameEaton Moeller series xEffect - FAZ MCBPart

no.FAZ-K50/4EAN4015082791049Product Length/Depth80 millimetreProduct height75.5 millimetreProduct width72 millimetreProduct weight0.49 kilogramCompliancesRoHS conformCertificationsIEC/EN 60898

IEC/EN 60947-2

IEC 61373

EN45545-2Product TradenamexEffect - FAZProduct TypeMCBProduct Sub TypeNoneDelivery

programApplicationSwitchgear for industrial and advanced commercial applications

xEffect - Switchgear for industrial and advanced commercial applicationsNumber of polesFour-poleNumber of poles (total)4Number of poles (protected)4Tripping characteristicKRelease characteristicKAmperage Rating50 ATypeFAZ

Miniature circuit breaker
Technical Data - Electrical
Voltage type AC
Voltage rating 240 V AC / 415 V AC
Voltage rating at DC 60 V DC (per pole)
Rated operational voltage (Ue) - max 400 V
Rated insulation voltage (Ui) 440 V
Rated impulse withstand voltage (Uimp) 4 kV
Frequency rating - min 50 Hz
Frequency rating - max 60 Hz
Rated switching capacity (IEC/EN 60947-2) 10 kA
Operational switching capacity 7.5 kA
Rated short-circuit breaking capacity (EN 60898) at 230 V 0 kA
Rated short-circuit breaking capacity (EN 60898) at 400 V 0 kA
Rated short-circuit breaking capacity (IEC 60947-2) at 230 V 10 kA
Rated short-circuit...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZ-K50/4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.