

INDUSTRIAL COMPONENT DATA

FAZ-PN-B13/1N 279148 Y7-279148 EATON ELECTRIC Miniature circuit breaker (MCB), 13A, 1Np, B-Char, AC

Brand: EATON - MOELLER | Manufacturer Part Number: FAZ-PN-B13/1N



Manufacturer	EATON - MOELLER
MPN / Reference	FAZ-PN-B13/1N
Catalog number	Y7-279148
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-47CEC00C7B
Generated	2026-08-06

Product Overview

Miniature circuit breaker (MCB), 13A, 1Np, B-Char, AC

FAZ-PN-B13/1N

Eaton Moeller series xEffect - FAZ-PN MCB. FAZ-PN, 1-pole+N, tripping characteristic: B, rated current In: 13 A

Miniature circuit breaker (MCB), FAZ-PN, 1-pole+N, tripping characteristic: B, rated current In: 13 A, Switchgear for industrial and advanced commercial applications

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Tertiary
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - FAZ-PN MCB Catalog Number 279148 Model Code FAZ-PN-B13/1N EAN 4015082791483 Product Length/Depth 80 mm Product Height 75.5 mm Product Width 17.5 mm Product Weight 0.112 kg
Compliances RoHS conform Certifications IEC/EN 60898
EN45545-2

IEC 61373 Product specifications

Type Application Switchgear for industrial and advanced commercial applications

xEffect - Switchgear for industrial and advanced commercial applications

Amperage Rating 13 A Voltage rating 240 V AC / 415 V AC Features Concurrently switching N-neutral

Additional equipment possible Frame 45 mm Pollution degree 2 Used with FAZ-PN

Miniature circuit breaker Mounting Method Top-hat rail IEC/EN 60715 Degree of protection IP40 (when fitted)

IP20 Rated impulse withstand voltage (Uimp) 4 kV Admissible back-up fuse - max 100 A gL/gG Terminal protection Finger and hand touch safe, DGUV VS3, EN 50274 Terminals (top and bottom) Twin-purpose terminals Tripping characteristic B Ambient operating temperature - max 75 °C Ambient operating temperature - min -25 °C Built-in depth 70.5 mm Connectable conductor cross section (multi-wired) - max 25 mm² Connectable conductor cross section (multi-wired) - min 1 mm² Connectable conductor cross section (solid-core) - max 25 mm² Connectable conductor cross section (solid-core) - min 1 mm² Current limiting class 3 Enclosure width 80 mm Frequency rating - max 60 Hz Frequency rating - min 50 Hz Direction of incoming supply As....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZ-PN-B13/1N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.