

INDUSTRIAL COMPONENT DATA

FAZ-XAA-NA12-110VAC 102037 Y7-102037 EATON ELECTRIC

Coil shooting, up to 40 A, 12-110V

Brand: EATON - MOELLER | Manufacturer Part Number: FAZ-XAA-NA12-110VAC



Manufacturer	EATON - MOELLER
MPN / Reference	FAZ-XAA-NA12-110VAC
Catalog number	Y7-102037
Category	Auxiliary device for distribution board devices
Minimum order	1 Pcs
Document ID	EO-36EB37A21C
Generated	2026-08-05

Product Overview

Coil shooting, up to 40 A, 12-110V

FAZ-XAA-NA12-110VAC

Eaton Distribution parts. Shunt release, up to 63A, 12-110V

Shunt release, for MCB up to 63A, voltage range 12-110V AC / 12-60V DC, standard front dimension 45 mm, mounting width 1 SU (17.5mm), top-hat rail mounting, terminal cross-section AWG 18-10

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 102037 Model Code FAZ-XAA-NA12-110VAC EAN

4015081019281 Product Length/Depth 105 mm Product Height 75.5 mm Product Width 17.7 mm Product Weight 0.11 kg

Compliances RoHS conform Certifications CSA (Class No. 1437-01)

North America (UL listed, CSA certified)

UL (Category Control Number DIHS, DIHS7)

CSA-C22.2 No. 5-09

IEC/EN 60898

UL (File No. E257181)

CE marking

UL 489

CSA (File No. 204453)

EN45545-2

IEC 61373 Product specifications

Type Application Switchgear for 110-V systems Accessory/spare part type Shunt release Degree of protection UL/CSA

Type: -

IP20 (IEC)

IP40 Frame Standard front dimension: 45 mm Frequency rating 50 Hz / 60 Hz Used with Shunt releases

Accessory

Accessory for miniature circuit breaker Mounting method For fitting on left to: FAZ-NA, FAZ-RT

Quick attachment with 2 latch positions for top-hat rail EN 50022 Additional equipment required Shunt release (for power circuit breaker) Terminal protection Busbar tag shroud to BGV A3 Terminal type Twin-purpose terminals Voltage range 12 V AC - 110 V AC Ambient operating temperature - max 40 °C Ambient operating temperature - min -5 °C Assembly width 1 TE Enclosure width 105 mm Number of contacts (change-over contacts) 0 Number of contacts (normally closed contacts) 1 Number of contacts (normally open contacts) 1 Number of poles at main contact unit - max 1 Number of switches (fault signal) 0 Voltage type AC/DC Functions Shunt release (for p...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZ-XAA-NA12-110VAC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.