

INDUSTRIAL COMPONENT DATA

FAZT-B12/1 240792 Y7-240792 EATON ELECTRIC Miniature circuit breaker (MCB), 12A, 1p, B-Char, AC

Brand: EATON - MOELLER | Manufacturer Part Number: FAZT-B12/1



Manufacturer	EATON - MOELLER
MPN / Reference	FAZT-B12/1
Catalog number	Y7-240792
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-54BBB4DDCC
Generated	2026-08-06

Product Overview

Miniature circuit breaker (MCB), 12A, 1p, B-Char, AC

FAZT-B12/1

Miniature circuit breaker (MCB), 12 A, 1p, characteristic: B

Miniature circuit breaker (MCB), FAZ-T, 1-pole, tripping characteristic: B, rated current In: 12 A, Switchgear for industrial and advanced commercial applications

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Industrial

Additional Product Information

Miniature circuit breaker (MCB), 12 A, 1p, characteristic: B
Miniature circuit breaker (MCB), FAZ-T, 1-pole, tripping characteristic: B, rated current In: 12 A, Switchgear for industrial and advanced commercial applications

General specifications
Product name Eaton Moeller series xEffect - FAZ-T MCB
Part no. FAZT-B12/1

EAN 4015082407926
Product Length/Depth 80 millimetre
Product height 75.5 millimetre
Product width 17.7 millimetre
Product weight 0.117 kilogram

Compliances RoHS conform
Certifications IEC/EN 60947-2

EN 45545-2

IEC 61373
Product Trade name xEffect - FAZ-T
Product Type MCB
Product Sub Type None

Delivery program Application Switchgear for industrial and advanced commercial applications

xEffect - Switchgear for industrial and advanced commercial applications
Number of poles Single-pole
Number of poles (total) 1
Number of poles (protected) 1
Tripping characteristic B
Release characteristic BA
Amperage Rating 12 A
Type FAZ-T

Miniature circuit breaker
Technical Data - Electrical
Voltage type AC
Voltage rating (IEC/EN 60898-1) 240 V AC
Voltage rating

(IEC/EN 60947-2)240 V AC Rated operational voltage (Ue) - max240 V Operational voltage (IEC/EN 60947-2) - max254 V
AC Operational voltage at DC (EC/EN 60947-2) - max60 V DC Rated insulation voltage (Ui)440 V Rated impulse withstand
voltage (Uimp)4 kV Frequency rating50 Hz / 60 Hz Frequency rating - min50 Hz Frequency rating - max60 Hz Rated switching
capacity (IEC/EN 60947-2) at max voltage rating15 kA Rated switching capacity (IEC/EN 60947-2)25 kA Rated switching
capacity (IEC/EN 6...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZT-B12/1 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.