

INDUSTRIAL COMPONENT DATA

FAZT-B13/4 240935 Y7-240935 EATON ELECTRIC Small circuit breaker

Brand: EATON - MOELLER | Manufacturer Part Number: FAZT-B13/4



Manufacturer	EATON - MOELLER
MPN / Reference	FAZT-B13/4
Catalog number	Y7-240935
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-941DC7718B
Generated	2026-08-06

Product Overview

Small circuit breaker

Miniature circuit breaker (MCB), 13 A, 4p, characteristic: B

Eaton Moeller series xEffect - FAZ-T MCB. FAZ-T, 4 pole, tripping characteristic: B, rated current In: 13 A

Miniature circuit breaker (MCB), FAZ-T, 4 pole, tripping characteristic: B, rated current In: 13 A, Switchgear for industrial and advanced commercial applications

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Industrial

Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - FAZ-T MCB Catalog Number 240935 Model Code FAZT-B13/4 EAN 4015082409357 Product Length/Depth 80 mm Product Height 75.5 mm Product Width 72 mm Product Weight 0.47 kg
Compliances RoHS conform Certifications IEC/EN 60947-2
EN45545-2

IEC 61373 Delivery program

Application Number of poles Four-pole Number of poles (total) 4 Number of poles (protected) 4 Tripping characteristic B
Release characteristic B Amperage Rating 13 A Type FAZ-T

Miniature circuit breaker

Technical data - electrical

Voltage type AC Voltage rating (IEC/EN 60898-1) 400 VAC Voltage rating (IEC/EN 60947-2) 415 V Rated operational

voltage (Ue) - max 440 V Operational voltage (IEC/EN 60947-2) - max 440 VAC Operational voltage at DC (EC/EN 60947-2) - max 60 VDC Rated insulation voltage (Ui) 440 V Rated impulse withstand voltage (Uimp) 4 kV Frequency rating 50 Hz / 60 Hz Frequency rating - min 50 Hz Frequency rating - max 60 Hz Rated switching capacity (IEC/EN 60947-2) at max voltage rating 15 kA Rated switching capacity (IEC/EN 60947-2) 25 kA Rated switching capacity (IEC/EN 60898-1) 15 kA Rated service short-circuit breaking capacity (IEC/EN 60898-1) 7.5 kA Rated service short-circuit breaking capacity (IEC/EN 60947-2) 7.5 kA Rated short-circuit breaking capacity (EN 60898) at 230 V 15 kA Rated short-circuit breaking capacity (EN 60898) at 400 V 15 kA Rated short-circuit breaking capacity (IEC 60947-2) at 230 V 25 kA Rated short-circuit breaking ca...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZT-B13/4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.