

INDUSTRIAL COMPONENT DATA

FAZT-D1/4 240968 Y7-240968 EATON ELECTRIC Miniature circuit breaker (MCB), 1A, 4p, D-Char, AC

Brand: EATON - MOELLER | Manufacturer Part Number: FAZT-D1/4



Manufacturer	EATON - MOELLER
MPN / Reference	FAZT-D1/4
Catalog number	Y7-240968
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-52245834AD
Generated	2026-08-05

Product Overview

Miniature circuit breaker (MCB), 1A, 4p, D-Char, AC

FAZT-D1/4

Eaton Moeller series xEffect - FAZ-T MCB. FAZ-T, 4 pole, tripping characteristic: D, rated current In: 1 A

Miniature circuit breaker (MCB), FAZ-T, 4 pole, tripping characteristic: D, rated current In: 1 A, Switchgear for industrial and advanced commercial applications

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Industrial

Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - FAZ-T MCB Catalog Number 240968 Model Code FAZT-D1/4 EAN

4015082409685 Product Length/Depth 80 mm Product Height 75.5 mm Product Width 72 mm Product Weight 0.448 kg

Compliances RoHS conform Certifications IEC/EN 60947-2

EN45545-2

IEC 61373 Delivery program

Application Number of poles Four-pole Number of poles (total) 4 Number of poles (protected) 4 Tripping characteristic D

Release characteristic D Amperage Rating 1 A Type FAZ-T

Miniature circuit breaker

Technical data - electrical

Voltage type AC Voltage rating (IEC/EN 60898-1) 400 VAC Voltage rating (IEC/EN 60947-2) 240 V AC / 415 V AC Rated

operational voltage (Ue) - max 415 V Operational voltage (IEC/EN 60947-2) - max 415 VAC Operational voltage at DC (EC/EN 60947-2) - max 60 VDC Rated insulation voltage (Ui) 440 V Rated impulse withstand voltage (Uimp) 4 kV Frequency rating 50 Hz / 60 Hz Frequency rating - min 50 Hz Frequency rating - max 60 Hz Rated switching capacity (IEC/EN 60947-2) 25 kA Rated short-circuit breaking capacity (EN 60898) at 230 V 15 kA Rated short-circuit breaking capacity (EN 60898) at 400 V 15 kA Rated short-circuit breaking capacity (IEC 60947-2) at 230 V 25 kA Rated short-circuit breaking capacity (IEC 60947-2) at 400 V 25 kA Overvoltage category III Pollution degree 2 Lifespan, electrical 4000 operations Direction of incoming supply As required Technical data - mechanical Frame 45 mm Enclosure width 80 mm Width in number of modula...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZT-D1/4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.