

INDUSTRIAL COMPONENT DATA

FBSMV-40/2/03-A 170211 Y7-170211 EATON ELECTRIC

Residual-current circuit breaker trip block for PLS. 40A, 2 ..

Brand: EATON - MOELLER | Manufacturer Part Number: FBSMV-40/2/03-A



Manufacturer	EATON - MOELLER
MPN / Reference	FBSMV-40/2/03-A
Catalog number	Y7-170211
Category	Residual current circuit breaker (RCCB)
Minimum order	1 Pcs
Document ID	EO-14D5C34FB5
Generated	2026-08-04

Product Overview

Residual-current circuit breaker trip block for PLS. 40A, 2 p, 300mA, type S/A
FBSMV-40/2/03-A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Industrial
--------------	---

Additional Product Information

Residual-current circuit breaker trip block for FAZ, 40A, 2p, 300mA, type AAttachable residual current circuit-breaker unit
FBSmV, 2 pole, Rated current In: 40 A, Rated short-circuit strength Icn:, Rated fault current I?N: 0.3 A, Switchgear for
industrial and advanced commercial applications

General specificationsProduct nameEaton Moeller series xEffect - FBSmV RCCB add-on unitPart

no.FBSMV-40/2/03-AEAN4015081667178Product Length/Depth90 millimetreProduct height75 millimetreProduct width70
millimetreProduct weight0.17 kilogramCompliancesRoHS conformCertificationsIEC 61373
EN45545-2

IEC/EN 61009Product TradenameFBSmVProduct TypeRCCB add-on unitProduct Sub TypeNoneDelivery
programApplicationSwitchgear for industrial and advanced commercial applications

xEffect - Switchgear for industrial and advanced commercial applicationsNumber of polesTwo-poleTripping
timeNon-delayedAmperage Rating40 ARated short-circuit strengthSame as connected FAZ up to max. 10 kAFault current
rating300 mASensitivity typePulse-current sensitivelmpulse withstand currentPartly surge-proof 250 ATTypeAdd-on residual
current protection unit
FBSmV

Type A Technical Data - Electrical
Voltage rating - min 240 V
Voltage rating - max 415 V
Rated operational voltage (U_e) -
max 240 V
Rated insulation voltage (U_i) 440 V
Rated impulse withstand voltage (U_{imp}) 4 kV
Rated fault current - min 0.3 A
Rated fault current - max 0.3 A
Frequency rating 50 Hz
Leakage current type A
Rated short-time withstand current (I_{cw}) 0 kA
10 kA
Surge current capa...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FBSMV-40/2/03-A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.