

INDUSTRIAL COMPONENT DATA

FBSMV-63/2/01-A 170210 Y7-170210 EATON ELECTRIC

Auxiliary contact, 1N/O+3N/C, surface mounting, screw connec..

Brand: EATON - MOELLER | Manufacturer Part Number: FBSMV-63/2/01-A



Manufacturer	EATON - MOELLER
MPN / Reference	FBSMV-63/2/01-A
Catalog number	Y7-170210
Category	Residual current circuit breaker (RCCB)
Minimum order	1 Pcs
Document ID	EO-DA0F6F91CE
Generated	2026-08-03

Product Overview

Auxiliary contact, 1N/O+3N/C, surface mounting, screw connection

FBSMV-63/2/01-A

Residual-current circuit breaker trip block for FAZ, 63A, 2p, 100mA, type A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Industrial
--------------	---

Additional Product Information

Residual-current circuit breaker trip block for FAZ, 63A, 2p, 100mA, type AAttachable residual current circuit-breaker unit
FBSmV, 2 pole, Rated current In: 63 A, Rated short-circuit strength Icn:, Rated fault current I?N: 0.1 A, Switchgear for
industrial and advanced commercial applications

General specificationsProduct nameEaton Moeller series xEffect - FBSmV RCCB add-on unitPart

no.FBSMV-63/2/01-AEAN4015081667161Product Length/Depth90 millimetreProduct height75 millimetreProduct width70
millimetreProduct weight0.211 kilogramCompliancesRoHS conformCertificationsEN45545-2
IEC 61373

IEC/EN 61009Product TradenameFBSmVProduct TypeRCCB add-on unitProduct Sub TypeNoneDelivery
programApplicationSwitchgear for industrial and advanced commercial applications

xEffect - Switchgear for industrial and advanced commercial applicationsNumber of polesTwo-poleTripping
timeNon-delayedAmperage Rating63 ARated short-circuit strengthSame as connected FAZ up to max. 10 kAFault current

rating100 mASensitivity typePulse-current sensitivelmpulse withstand currentPartly surge-proof 250 ATypeAmbient
temperature hint: Starting at 40 °C, the max. permissible continuous current decreases by 3% for every 1 °CTechnical Data
- ElectricalVoltage rating - min240 VVoltage rating - max415 VRated operational voltage (Ue) - max240 VRated insulation
voltage (Ui)440 VRated impulse withstand voltage (Uimp)4 kVRated fault current - min0.1 ARated fault current - max0.1
AFrequency rating50 HzLeakage current typeARate...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FBSMV-63/2/01-A with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.